



Declaration of Performance

No.: 10-374-100-01

1. Unique identification code of the product-type:

CEMENTITIOUS SCREEDS CT - C30 — F5

2. Type, batch, or serial number or any other element allowing the construction product to be identified in accordance with Article 11 (4):

BOSTIK RENO QUICK, BOSTIK XPS

See on the packaging: date of manufacture, batch number, manufacturing center

3. **Use or intended use of the construction product in accordance with the applicable harmonized technical specification, as specified by the manufacturer:**

Cement-based screed materials, not intended for wear surfaces, for internal use in buildings

4. **Name, company name or registered trade mark and contact address of the manufacturer in accordance with Article 11 (5):**

Société BOSTIK, le Jade Building - 253 Av du président Wilson — F-93211 La Plaine Saint-Denis Cedex
www.bostik.fr

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks referred to in Article 12 (2):

Not applicable

6. System or systems of Assessment and Verification of Constancy of Performance of the construction product in accordance with Annex V:

Level 3

7. **In the case of a declaration of performance for a construction product covered by a harmonized standard:**

The notified CEBTP (Experimental Center of Research and Studies for Building and Public Works Industry) laboratory No. 0074 determined the product-type on the basis of type tests according to system 3 and issued the test report.

8. **In the case of a declaration of performance for a construction product for which a European technical assessment has been issued:**

Not applicable



Declaration of Performance

9. Declared performance:

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	A1	EN 13813:2002
Emission of corrosive substances or corrosivity of screed materials	Voir FDS	
Water permeability	NPD	
Water vapor permeability	NPD	
Mechanical strength		
- Compressive strength	≥ C 30	
- Bending strength	≥ F 5	
- Wear resistance (for wear surfaces)	NPD	
Sound insulation		
- Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	

10. The performance of the product identified in points 1 and 2 shall comply with the declared performance indicated in point 9.

This declaration of performance shall be drawn up under the sole responsibility of the manufacturer identified

in point 4

Signed for and on behalf of the manufacturer by:

Name and position of company /stamp/

representative

Place and Date

/signature/