

## Declaration of Performance

No.: 40-605-300-01

**1. Unique identification code of the product-type:**

Elastic sealant for facade elements, suitable for indoor use only.

**2. Type, batch, or serial number or any other element allowing the construction product to be identified in accordance with Article 11 (4):**

**30601522 MSP 106 INVISIBLE**

See packaging: batch number, date of manufacture and manufacturing center.

**3. Use or intended use of the construction product in accordance with the applicable harmonized technical specification, as specified by the manufacturer:**

Joint sealants for non-structural use between facade elements, for indoor use only.

**4. Name, company name or registered trade mark and contact address of the manufacturer in accordance with Article 11 (5):**

Société BOSTIK, le Jade Building — 253 Av du président Wilson — F-9321 La Plaine Saint-Denis Cedex  
[www.bostik.fr](http://www.bostik.fr)

**5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks referred to in Article 12 (2):**

Not applicable

**6. System or systems of Assessment and Verification of Constancy of Performance of the construction product in accordance with Annex V:**

Level 4

**7. In the case of a declaration of performance for a construction product covered by a harmonized standard:**

The manufacturer has determined the product-type on the basis of type tests and factory production control according to system 4.

**8. In the case of a declaration of performance for a construction product for which a European technical assessment has been issued:**

Not applicable

## Déclaration des Performances

### 9. Declared performance:

Sealants for facade elements

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	Class F	EN 15651-1: 2012
Release of hazardous substances	See SDS	
Water and air tightness		
Volume loss	≤ 45%	
Resistance to casting	≤ 5 mm	
Adhesion/cohesion, deformation properties under traction after immersion in water (23°C)	≥ 25%	
Sustainability	Compliant	

10. The performance of the product identified in points 1 and 2 shall comply with the declared performance indicated in point 9.

**This declaration of performance shall be drawn up under the sole responsibility of the manufacturer identified in point 4.**

**Signed for and on behalf of the manufacturer by:**

Name and position of company representative

Place and Date

**/signature/ /stamp/**