



## Declaration of Performance

No.: 10-374-100-01

**1. Unique identification code of the product-type:**

CEMENTITIOUS SCREEDS CT - C30 — F5

**2. Type, batch, or serial number or any other element allowing the construction product to be identified in accordance with Article 11 (4):**

BOSTIK RENO QUICK, BOSTIK XPS

See on the packaging: date of manufacture, batch number, manufacturing center

**3. Use or intended use of the construction product in accordance with the applicable harmonized technical specification, as specified by the manufacturer:**

Cement-based screed materials, not intended for wear surfaces, for internal use in buildings

**4. Name, company name or registered trade mark and contact address of the manufacturer in accordance with Article 11 (5):**

Société BOSTIK, le Jade Building - 253 Av du président Wilson — F-93211 La Plaine Saint-Denis Cedex  
[www.bostik.fr](http://www.bostik.fr)

**5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks referred to in Article 12 (2):**

Not applicable

**6. System or systems of Assessment and Verification of Constancy of Performance of the construction product in accordance with Annex V:**

Level 3

**7. In the case of a declaration of performance for a construction product covered by a harmonized standard:**

The notified CEBTP (Experimental Center of Research and Studies for Building and Public Works Industry) laboratory No. 0074 determined the product-type on the basis of type tests according to system 3 and issued the test report.

**8. In the case of a declaration of performance for a construction product for which a European technical assessment has been issued:**

Not applicable



## Declaration of Performance

### 9. Declared performance:

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	A1	EN 13813:2002
Emission of corrosive substances or corrosivity of screed materials	Voir FDS	
<b>Water permeability</b>	NPD	
Water vapor permeability	NPD	
<b>Mechanical strength</b>		
- Compressive strength	$\geq C 30$	
- Bending strength	$\geq F 5$	
- Wear resistance (for wear surfaces)	NPD	
Sound insulation		
- Sound absorption	NPD	
Thermal resistance	NPD	
<b>Chemical resistance</b>	NPD	

10. The performance of the product identified in points 1 and 2 shall comply with the declared performance indicated in point 9.

**This declaration of performance shall be drawn up under the sole responsibility of the manufacturer identified**

in point 4

Signed for and on behalf of the manufacturer by:

Name and position of company

representative Place and Date

7/6/2013 /signature/ / stamp/