

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK PU GUNFOAM FLEX Supercedes Date: 02-Feb-2016

Revision Date 06-Jan-2017 Version 2

1.1. Product Identifier

Product NameBOSTIK PU GUNFOAM FLEXPure substance/mixtureMixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended useBuilding and construction work.Uses advised againstNone known.

1.3. Details of the supplier of the safety data sheet

Company Name Bostik BV De Voerman 8 PO Box 303 5215 MH's-Hertogenbosch, The Netherlands Tel: +31 736 244 244 Fax: +31 736 244 344

E-mail address

SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

No information available

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin Corrosion/Irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)
Aerosols	Category 1 - (H222)

Unknown acute toxicity Unknown aquatic toxicity 100 % of the mixture consists of ingredient(s) of unknown toxicity Contains 0 % of components with unknown hazards to the aquatic environment

2.2. Label Elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains Isocyanic acid, polymethylenepolyphenylene ester

BOSTIK PU GUNFOAM FLEX Supercedes Date: 02-Feb-2016



Signal Word DANGER

Hazard statements

- H222 Extremely flammable aerosol
- H229 Pressurised container: May burst if heated
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335 May cause respiratory irritation
- H351 Suspected of causing cancer
- H373 May cause damage to organs through prolonged or repeated exposure
- EUH204 Contains isocyanates. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

- P201 Obtain special instructions before use
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P211 Do not spray on an open flame or other ignition source
- P251 Do not pierce or burn, even after use
- P260 Do not breathe spray
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P308 + P313 IF exposed or concerned: Get medical advice/attention

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
- P403 Store in a well-ventilated place
- P501 Dispose of contents/container to industrial incineration plant

Special provisions concerning the labelling of certain mixtures

Placed on the market in aerosol containers or in containers fitted with a sealed spray attachment

See section 7 for more information

Persons already sensitised to diisocyanates may develop allergic reactions when using this product

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. Type A according to standard EN 14387) is used

2.3. Other Hazards

General Hazards

No information available.

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

BOSTIK PU GUNFOAM FLEX Supercedes Date: 02-Feb-2016

Mixture

3.2 Mixtures

Chemical Name	EC No	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Isocyanic acid, polymethylenepolyphenylen e ester	-	9016-87-9	40 - <80	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tox. 4 (H332)	Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 ::	Exempt(P)
2-Propanol, 1-chloro-, phosphate (3:1)	237-158-7	13674-84-5	20 - 25	Acute Tox. 4 (H302)		01-2119480419-30 -XXXX
Propane	200-827-9	74-98-6	10 - <20	Flam. Gas 1 (H220) Press. Gas		01-2119486944-21 -XXXX
Isobutane	200-857-2	75-28-5	10 - <20	Flam. Gas 1 (H220) Press. Gas		01-2119485395-27 -XXXX
Dimethyl ether	204-065-8	115-10-6	10 - <20	Flam. Gas 1 (H220) Press. Gas		01-2119472128-37 -XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classifed, however, the substance is listed in section 3 as it has an OEL.

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
Inhalation	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.
Skin Contact	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
Eye contact	Keep eye wide open while rinsing. If symptoms persist, call a doctor. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes.
Ingestion	Rinse mouth. Drink plenty of water. Do NOT induce vomiting. If symptoms persist, call a doctor. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a doctor.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

BOSTIK PU GUNFOAM FLEX Supercedes Date: 02-Feb-2016

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors

Keep victim warm and quiet.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire. Dry chemical or CO2. Water spray, fog or regular foam. Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

Large Fire Water spray or fog.

Unsuitable Extinguishing Media Full water jet

5.2. Special hazards arising from the substance or mixture

Ruptured cylinders may rocket. Some may burn but none ignite readily.

Hazardous Combustion Products Carbon monoxide. Nitrogen oxides (NOx). Hydrogen chloride. Hydrogen cyanide. Carbon dioxide (CO2). Formaldehyde.

5.3. Advice for firefighters

Caution! Container under pressure. Heating causes rise in pressure with risk of bursting. Cool container with water spray.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions

Remove all possible sources of ignition in the surrounding area. Ensure adequate ventilation, especially in confined areas.

Ventilate the area.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Use water spray to reduce vapours or divert vapour cloud drift. Avoid allowing water runoff to contact spilled material. Prevent entry into waterways, sewers, basements or confined areas.

6.3. Methods and material for containment and cleaning up

Methods for Containment If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

Methods for cleaning up Do not direct water at spill or source of leak.

6.4. Reference to other sections

Reference to other sections	Section 7: HANDLING AND STORAGE
	Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
	Section 13: DISPOSAL CONSIDERATIONS

BOSTIK PU GUNFOAM FLEX

Supercedes Date: 02-Feb-2016

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation, especially in confined areas. Use only in well-ventilated areas. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Recommended storage temperature. 10 - 35 °C. Observe local regulations / instructions for storage of pressurized containers. Keep from freezing.

7.3. Specific end use(s)

Other Information

Recommendation(s). Observe technical data sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical Name	European Union
Dimethyl ether	TWA: 1000 ppm
115-10-6	TWA: 1920 mg/m ³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available. (PNEC)

8.2. Exposure controls

Engineering Controls	Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipment Eye/Face Protection Hand Protection	t Tight sealing safety goggles. Face protection shield. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Skin and Body Protection	Antistatic footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic or rubber. Suitable protective clothing. Apron.
Respiratory Protection	Provide adequate ventilation. In case of inadequate ventilation wear respiratory protection.

Environmental Exposure Controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance

Aerosol Foam

BOSTIK PU GUNFOAM FLEX Supercedes Date: 02-Feb-2016

Colour	No information available	
Odour	Characteristic	
Odour Threshold	No information available	
Property	Values	Remarks • Method
pH	No information available	
Melting point/freezing point	No information available	
Boiling Point	No information available	
Flash Point	No information available	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper Flammability Limit	16	
Lower Flammability Limit	3	
Vapour Pressure	605	kPa
Vapour Density	No information available	
Specific Gravity	No information available	
Water Solubility	Immiscible in water	
Solubility in Other Solvents	No information available	
Partition Coefficient	No information available	
Autoignition Temperature	235 °C / 455 °F	
Decomposition Temperature	No information available	
Explosive Properties	No information available	
Explosive Limits	No information available	
Upper	No information available	
Lower	No information available	
Oxidising Properties	No information available	
Kinematic Viscosity	No information available	
Dynamic Viscosity	No information available	
9.2. Other information		
Softening Point	No information available	
Molecular Weight	No information available	
Solvent content (%)	No information available	
Solid content (%)	No information available	
Density	1.048 g/cm ³	
Bulk Density	No Data Available	
VOC content (%)	155.87 g/L	

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions.

10.2. Chemical stability

Stable under normal conditions.

Explosion Data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

10.3. Possibility of hazardous reactions

Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Heating causes rise in pressure with risk of bursting.

BOSTIK PU GUNFOAM FLEX Supercedes Date: 02-Feb-2016

10.5. Incompatible materials

Acids. Bases. Strong oxidising agents. Amines, Alcohols. Water. Acid anhydrides. Strong acids.

10.6. Hazardous decomposition products

Hydrogen cyanide. Hydrogen chloride. Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Formaldehyde.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Product Information

Harmful by inhalation.

Inhalation Eye contact Skin Contact Ingestion Sensitisation	No Data Available. No Data Available. No Data Available. No Data Available. May cause sensitisation by inhalation. May cause sensitisation by skin contact.	
Skin Corrosion/Irritation	Irritating to skin.	
Serious eye damage/eye irritation	Irritant effect on the eyes.	
Sensitisation	Not applicable.	
Germ Cell Mutagenicity	Not applicable.	
Carcinogenicity	Contains a known or suspected carcinogen.	
Reproductive Toxicity	No information available.	
STOT - Single Exposure	No information available.	
STOT - Repeated Exposure	No information available.	
Target Organ Effects	Heart, Central nervous system.	
Aspiration Hazard	No information available.	
Numerical measures of toxicity		
Acute Toxicity		
The following values are calculated ATEmix (oral) ATEmix (dermal) ATEmix (inhalation-dust/mist)	d based on chapter 3.1 of the GHS document 5,250.00 mg/kg 4,305.00 mg/kg 1.50 mg/l	
Unknown acute toxicity100 % of the mixture consists of ingredient(s) of unknown toxicity.30 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.30 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.80 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapour).50 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).		

Component Information

Toxicity Data

Data obtained on the component(s) include

BOSTIK PU GUNFOAM FLEX

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isocyanic acid,	LD 50 > 10000 mg/kg (Rat)	LD 50 > 9400 mg/kg (Rabbit)	=1.5 mg/m³ (Rat)4 h
polymethylenepolyphenylene ester	· ·		
9016-87-9			
2-Propanol, 1-chloro-, phosphate	= 1500 mg/kg (Rat)	= 1230 mg/kg (Rabbit)	> 4.6 mg/L (Rat)4 h
(3:1)			- · · ·
13674-84-5			

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity

No information available

Component Information

Data obtained on the component(s) include

Chemical Name	Algae/aquatic plants	Fish	Crustacea	M-Factor
Isocyanic acid, polymethylenepolyphenylen e ester 9016-87-9	-	CL50 (96h) >1000 mg/L Fish (Danio rerio)	-	
2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5	EC50 72 h = 45 mg/L (Desmodesmus subspicatus)	LC50 96 h = 30 mg/L (Poecilia reticulata static)	EC50 48 h = 63 mg/L (Daphnia magna)	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Partition coefficient No information available

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other Adverse Effects

No information available

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Disposal should be in accordance with applicable regional, national and local laws and regulations.

BOSTIK PU GUNFOAM FLEX Supercedes Date: 02-Feb-2016	Revision Date 06-Jan-2017 Version 2
Contaminated Packaging	Improper disposal or reuse of this container may be dangerous and illegal.
European Waste Catalogue	08 05 01* waste isocyanates 16 05 04* gases in pressure containers (including halons) containing dangerous substances
Other Information	Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORTATION INFORMATION

ADR 14.1 UN/ID no 14.2 Proper Shipping Name 14.3 Hazard Class Hazard Labels 14.4 Packing Group Description 14.5 Environmental Hazard 14.6 Special Provisions Classification Code Tunnel restriction code Limited Quantity (LQ)	UN1950 Aerosols 2.1 2.1 Not regulated UN1950, Aerosols, 2.1 Not applicable 190, 327, 344, 625 5F (D) 1 L	
IMDG 14.1 UN/ID no 14.2 Proper Shipping Name 14.3 Hazard Class 14.4 Packing Group Description 14.5 Marine Pollutant 14.6 Special Provisions Limited Quantity (LQ) EmS-No 14.7 Transport in bulk according	UN1950 Aerosols 2.1 Not regulated UN1950, Aerosols, 2.1 Np 63,190, 277, 327, 344, 959 See SP277 F-D, S-U to Annex II of MARPOL 73/78 and the IBC Code	No information available
RID14.1UN/ID no14.2Proper Shipping Name14.3Hazard Class14.4Packing Group Description14.5Environmental Hazard Classification Code14.6Special Provisions Limited Quantity (LQ)	UN1950 Aerosols 2.1 Not regulated UN1950, Aerosols, 2.1 Not applicable 5F None 1 L	
ICAO (air) 14.1 UN/ID no 14.2 Proper Shipping Name 14.3 Hazard Class 14.4 Packing Group Description 14.5 Environmental Hazard 14.6 Special Provisions	UN1950 Aerosols 2.1 Not regulated UN1950, Aerosols, 2.1 Not applicable A145, A167	
IATA 14.1 UN/ID no 14.2 Proper Shipping Name 14.3 Hazard Class 14.4 Packing Group Description 14.5 Environmental Hazard	UN1950 Aerosols, flammable 2.1 Not regulated UN1950, Aerosols, flammable, 2.1 Not applicable	

14.6 Special Provisions	A145, A
Limited Quantity (LQ)	30 kg G
ERG Code	10L

145, A167, A802 0 kg G 0I

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants Not applicable

National Regulations

France

Occupational Illnesses (R-463-3, France)

Chemical Name	French RG number
Isocyanic acid, polymethylenepolyphenylene ester	RG 62
9016-87-9	

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV Flammable liquid (R10), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 3

BOSTIK PU GUNFOAM FLEX Supercedes Date: 02-Feb-2016

Water hazard class (WGK) WGK 3

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H302 - Harmful if swallowed

H335 - May cause respiratory irritation

- H373 May cause damage to organs through prolonged or repeated exposure if inhaled
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H317 May cause an allergic skin reaction
- H351 Suspected of causing cancer if inhaled
- H332 Harmful if inhaled

Legend

SVHC: Substances of Very High Concern for Authorisation:

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWATWA (time-weighted average)STELCeilingMaximum limit value*PBTPersistent, Bioaccumulative, and Toxic (PBT) ChemicalsSTOT (RE):Specific target organ toxicity - Repeated exposureSTOT (SE):Specific target organ toxicity - Single exposureEWC:European Waste Catalogue

STEL (Short Term Exposure Limit) Skin designation

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By	Product Safety & Regulatory Affairs
Revision Date	06-Jan-2017
Indication of changes	
Revision Note	SDS sections updated: 2, 3, 11.
Training Advice	No information available
Additional information	No information available

This safety data sheet complies with the requirements of: Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

BOSTIK PU GUNFOAM FLEX Supercedes Date: 02-Feb-2016

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet