

BOSTIK SOL CONTACT
Supersedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2

1.1. Product Identifier

Product Name BOSTIK SOL CONTACT
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Contact adhesives.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik SA
Immeuble "Le Jade"
253 Avenue du President Wilson
93211 La Plaine Saint Denis
France
Tel: +33 (0)1 55 99 90 00
Fax: +33 (0)1 55 99 90 01

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone No information available

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Corrosion/Irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable Liquids	Category 2 - (H225)

Unknown acute toxicity 73 % of the mixture consists of ingredient(s) of unknown toxicity
Unknown aquatic toxicity Contains 0 % of components with unknown hazards to the aquatic environment

2.2. Label Elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains : Methylcyclohexane, Acetone, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane, Methyl ethyl ketone

Safety Data Sheet

BOSTIK SOL CONTACT
Supersedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2



Signal Word
DANGER

Hazard statements

H225 - Highly flammable liquid and vapour
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects
EUH208 - Contains rosin. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children
P280 - Wear protective gloves and eye/face protection
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention
P271 - Use only outdoors or in a well-ventilated area
P261 - Avoid breathing vapours
P312 - Call a POISON CENTER or doctor if you feel unwell
P101 - If medical advice is needed, have product container or label at hand
P403 - Store in a well-ventilated place
P273 - Avoid release to the environment
P501 - Dispose of contents/ container to an approved waste disposal plant

Special provisions concerning the labelling of certain mixtures

This product requires tactile warnings if supplied to the general public

2.3. Other Hazards

General Hazards

In use may form flammable/explosive vapour-air mixture.

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical Name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Methylcyclohexane	203-624-3	108-87-2	>25 - <40	Skin Irrit. 2 (H315) STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411)		01-2119556887-18 -XXXX

Safety Data Sheet

BOSTIK SOL CONTACT
Supersedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2

				Flam. Liq. 2 (H225)		
Acetone	200-662-2	67-64-1	20 - 25	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)		01-2119471330-49 -XXXX
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane	921-024-6	--	10 - <20	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225)		01-2119475514-35 -XXXX
Methyl ethyl ketone	201-159-0	78-93-3	5 - <10	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)		01-2119457290-43 -XXXX
Rosin	232-475-7	8050-09-7	0.1- <1	Skin Sens. 1 (H317)		01-2119480418-32 -XXXX
Hexane	203-777-6	110-54-3	0.1- <1	Skin Irrit. 2 (H315) Repr. 2 (H361f) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	STOT RE 2 :: C>=5%	01-2119480412-44 -XXXX

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Immediate medical attention is required. In case of accident or being unwell, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a doctor.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapours.
Skin Contact	Wash off immediately with plenty of water. Wash contaminated clothing before reuse. If skin irritation persists, call a doctor. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a doctor. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.
Ingestion	Immediate medical attention is not required. Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

Safety Data Sheet

BOSTIK SOL CONTACT
Supercedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use CO₂, dry chemical, or foam.

Unsuitable Extinguishing Media

Use water spray or fog; do not use straight streams Do not use a solid water stream as it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). EXTREMELY FLAMMABLE.

5.3. Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions

Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak.

Water spray may reduce vapour; but may not prevent ignition in closed spaces.

For emergency responders

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Pick up and transfer to properly labelled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

6.4. Reference to other sections

Reference to other sections

See Section 12: ECOLOGICAL INFORMATION
Section 7: HANDLING AND STORAGE
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust

Safety Data Sheet

BOSTIK SOL CONTACT
Supercedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2

ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapours/spray.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep tightly closed in a dry and cool place. Keep in properly labelled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Other Information

Recommendation(s). Observe technical data sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical Name	European Union
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³
Hexane 110-54-3	TWA: 20 ppm TWA: 72 mg/m ³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Tight sealing safety goggles. Face protection shield.
Skin and Body Protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic or rubber. Suitable protective clothing. Apron.
Respiratory Protection Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental Exposure Controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid
Appearance Viscous
Colour No information available
Odour Solvent
Odour Threshold No information available

Property	Values	Remarks • Method
pH	No information available	

Safety Data Sheet

BOSTIK SOL CONTACT
Supercedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2

Melting point/freezing point	No information available	
Boiling Point	≥ 56 °C / 133 °F	
Flash Point	≥ -20 °C / -4 °F	CC (closed cup)
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	Not applicable for liquids
Flammability Limit in Air		
Upper Flammability Limit	13	
Lower Flammability Limit	1	
Vapour Pressure	110	
Vapour Density	No information available	
Relative Density	No information available	
Water Solubility	Insoluble in water	
Solubility in Other Solvents	Acetone, Methyl ethyl ketone	
Partition Coefficient	No information available	
Autoignition Temperature	No information available	
Decomposition Temperature	No information available	
Explosive Properties	No information available	
Explosive Limits	No information available	
Upper	No information available	
Lower	No information available	
Oxidising Properties	No information available	
Kinematic Viscosity	> 700 mm ² /s	@ 40°C
Dynamic Viscosity	1700 - 2300 mPa s	@ 20 °C

9.2. Other information

Softening Point	No information available
Molecular Weight	No information available
Solvent content (%)	No information available
Solid content (%)	≥ 19.5
Density	0.815 g/cm ³
Bulk Density	No Data Available
VOC content (%)	

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Stable under recommended storage conditions.

10.2. Chemical stability

Stable under recommended storage conditions.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by friction, heat, sparks or flames.

10.3. Possibility of hazardous reactions

Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

Strong acids and bases.

10.6. Hazardous decomposition products

Safety Data Sheet

BOSTIK SOL CONTACT
Supersedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2

None under normal use conditions.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Product Information

No information or data specific to the product on this toxicological (health) effect is available.

Inhalation	May cause drowsiness or dizziness.
Eye contact	Irritating to eyes. Avoid contact with eyes.
Skin Contact	Irritating to skin. Avoid contact with skin.
Ingestion	No Data Available.
Sensitisation	May cause sensitisation of susceptible persons.

Skin Corrosion/Irritation Not applicable.

Serious eye damage/eye irritation Not applicable.

Sensitisation Not applicable.

Germ Cell Mutagenicity Not applicable.

Carcinogenicity Not applicable.

Reproductive Toxicity No information available.

STOT - Single Exposure No information available.

STOT - Repeated Exposure No information available.

Target Organ Effects Central nervous system, Eyes, Respiratory system, Skin.

Aspiration Hazard No information available.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	4,706.00 mg/kg
ATEmix (dermal)	5,179.00 mg/kg
ATEmix (inhalation-dust/mist)	220.90 mg/l

Unknown acute toxicity 73 % of the mixture consists of ingredient(s) of unknown toxicity.

0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

3 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

73 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

49 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapour).

51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Component Information

Toxicity Data Data obtained on the component(s) include

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methylcyclohexane 108-87-2	> 3200 mg/kg (Rat)	>2920 mg/Kg bw (rat) 24 hour	>23 mg/l (vapour) (Rat- OECD 403)
Acetone 67-64-1	= 5800 mg/kg (Rat)	>15800 mg/Kg (rat)	= 79 mg/l(Rat) 4 h
Hydrocarbons, C6-C7, n-alkanes,	LD50 >5840 mg/kg (Rat)	LD50 >2800-3100 mg/kg (Rat)	-

Safety Data Sheet

BOSTIK SOL CONTACT
Supersedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2

isoalkanes, cyclic, <5% n-hexane --			
Methyl ethyl ketone 78-93-3	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
Rosin 8050-09-7	>2800 mg/Kg (rat)	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h
Hexane 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity

Toxic to aquatic life with long lasting effects

Component Information

Data obtained on the component(s) include

Chemical Name	Algae/aquatic plants	Fish	Crustacea	M-Factor
Methylcyclohexane 108-87-2	10 mg/l (Pseudokirchneriella subcapitata - OECD 201)	2.07 mg/l (Oryzias latipes)	3 mg/l (Daphnia magna - OECD 202)	
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane --	EL50 (72h)= 26 mg/L (Pseudokirchneriella subcapitata) OECD 201	LL50 (96h) =12 mg/L Fish (Oncorhynchus mykiss) OECD 203	EL50 (48h) =3mg/L (Daphnia magna) OECD 202	
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50 96 h 3130 - 3320 mg/L (Pimephales promelas flow-through)	EC50 48 h > 308 mg/L (Daphnia magna)	
Rosin 8050-09-7	EC50 72 h = 400 mg/L (Desmodesmus subspicatus)	LC50 (96h) >10mg/L Fish (Danio rerio)	EC50 48 h >100 mg/L (Daphnia magna)	
Hexane 110-54-3	-	LC50 96 h 2.1 - 2.98 mg/L (Pimephales promelas flow-through)	EC50 24 h > 1000 mg/L (Daphnia magna)	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Partition coefficient

No information available

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other Adverse Effects

No information available

Endocrine Disruptor Information

Safety Data Sheet

BOSTIK SOL CONTACT
Supersedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Improper disposal or reuse of this container may be dangerous and illegal.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other Information	Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORTATION INFORMATION

ADR

14.1 UN/ID no	UN1133
14.2 Proper Shipping Name	Adhesives, Environmentally Hazardous
14.3 Hazard Class	3
Hazard Labels	3
14.4 Packing Group	III
Description	UN1133, Adhesives, 3, III, (D/E), Environmentally Hazardous
14.5 Environmental Hazard	yes
14.6 Special Provisions	640E
Classification Code	F1
Tunnel restriction code	(D/E)
Limited Quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	30

IMDG

14.1 UN/ID no	UN1133
14.2 Proper Shipping Name	Adhesives (Methylcyclohexane), Marine Pollutant
14.3 Hazard Class	3
14.4 Packing Group	III
Description	UN1133, Adhesives (Methylcyclohexane), 3, III, (-20°C c.c.), Marine Pollutant
14.5 Marine Pollutant	PP
14.6 Special Provisions	223, 955
Limited Quantity (LQ)	5 L
EmS-No	F-E, S-D
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

RID

14.1 UN/ID no	UN1133
14.2 Proper Shipping Name	Adhesives, Environmentally Hazardous
14.3 Hazard Class	3
Hazard Labels	3
14.4 Packing Group	III
Description	UN1133, Adhesives, 3, III, Environmentally Hazardous
14.5 Environmental Hazard	yes
Classification Code	F1
14.6 Special Provisions	640E
Limited Quantity (LQ)	5 L

ICAO (air)

14.1 UN/ID no	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Hazard Class	3

Safety Data Sheet

BOSTIK SOL CONTACT
Supercedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2

14.4 Packing Group III
Description UN1133, Adhesives, 3, III
14.5 Environmental Hazard yes
14.6 Special Provisions A3

IATA

14.1 UN/ID no UN1133
14.2 Proper Shipping Name Adhesives
14.3 Hazard Class 3
14.4 Packing Group III
Description UN1133, Adhesives, 3, III
14.5 Environmental Hazard yes
14.6 Special Provisions A3
Limited Quantity (LQ) 10 L
ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

or

P5b - FLAMMABLE LIQUIDS

or

P5c - FLAMMABLE LIQUIDS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Safety Data Sheet

BOSTIK SOL CONTACT
Supercedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2

Persistent Organic Pollutants
Not applicable

National Regulations

France

Occupational Illnesses (R-463-3, France)

Chemical Name	French RG number
Methylcyclohexane 108-87-2	RG 84
Acetone 67-64-1	RG 84
Methyl ethyl ketone 78-93-3	RG 84
Rosin 8050-09-7	RG 65, RG 66
Hexane 110-54-3	RG 59, RG 84

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

Flammable liquid (R11), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 4

TRGS - 510 Storage Class

Storage Class 3 : Flammable liquids

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical Name	Netherlands
Hexane 110-54-3	Fertility (Category 2)

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H304 - May be fatal if swallowed and enters airways
H411 - Toxic to aquatic life with long lasting effects
H225 - Highly flammable liquid and vapour
H361f - Suspected of damaging fertility
H373 - May cause damage to organs through prolonged or repeated exposure if inhaled
H319 - Causes serious eye irritation
H317 - May cause an allergic skin reaction
EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

SVHC: Substances of Very High Concern for Authorisation:

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Safety Data Sheet

BOSTIK SOL CONTACT
Supersedes Date: 28-Nov-2016

Revision Date 24-Apr-2017
Version 2

TWA Ceiling	TWA (time-weighted average) Maximum limit value	STEL *	STEL (Short Term Exposure Limit) Skin designation
----------------	----------------------------------------------------	-----------	------------------------------------------------------

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
STOT (RE): Specific target organ toxicity - Repeated exposure
STOT (SE): Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 24-Apr-2017

Indication of changes

Revision Note SDS sections updated: 2.

Training Advice Provide adequate information, instruction, and training for operator

Additional information No information available

This safety data sheet complies with the requirements of: Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet