



# MS Adhesives and Sealants range

### **BRANZ APPRAISED**

Bostik MS technology enables high-performance adhesives and sealants to be used in a wide range of applications both indoors and outdoors. These solvent-free, low VOC, low odour products elastically seal most building materials and surfaces. Ideal for green builds, Bostik MS adhesives and sealants are easily applied with low temperature gunning.



bostik.co.nz

## **Bostik MS Adhesives and Sealants range**



#### MS SAFE FIX Solvent free, high performance MS construction adhesive

BRANZ appraised, multi-purpose, heavy duty, MS-based adhesive for construction & building. Elastically seals most building materials and surfaces. Green Star compliant. Exceptionally high initial grab. Available in cartridge only.

PRODUCT CODE	COLOUR	ТҮРЕ	SIZE	UNITS/CTN	
30605494	White	Cartridge	430g	12	
KEY FEATURES		RECOMMENDED USES			
<ul> <li>BRANZ appraisal 662 for structural loads and durability</li> <li>Ideal for green buildings - Low VOC, odour-free, solvent, silicone and isocyanate-free</li> <li>Exceptionally high initial grab - Ideal when using no mechanical fasteners (check with Bostik technical)</li> <li>Adheres to most common building substrates, polystyrene safe.</li> <li>Easy, low temperature gunning.</li> </ul>		<ul> <li>General construction adhesive</li> <li>For fixing wall panels, floors, and door frames to most common building substrates.</li> <li>For adhering solvent sensitive substrates (such as mirrors and polystyrene)</li> <li>Elastically bonding different materials with each other</li> <li>Bonding granite, marble and tiles</li> <li>Bonding skirting of many different types</li> </ul>			
<ul> <li>Highly flexible, paintable, very low shrinkage, non- slump</li> <li>Interior/Exterior – all weather, UV resistant</li> </ul>					
• One component					

#### **MS SAFE SEAL** Solvent free, high performance MS construction sealant.

BRANZ appraised, multi-purpose, heavy duty, MS-based sealant for construction & building. Highly elastic and flexible. Green Star compliant - Low VOC, odour-free, isocyanate-free and solvent free. Adheres to most common building substrates. Fully paintable. Available in cartridge and sausage in white, grey and black.

PRODUCT CODE	COLOUR	ТҮРЕ	SIZE	UNITS/CTN
30605491	White	Cartridge	430g	12
30804179		Sausage	900g	12
30605492	Grey	Cartridge	430g	12
30804013		Sausage	900g	12
30605493	Black	Cartridge	430g	12
30804011		Sausage	900g	12
KEY FEATURES		RECOMMENDED USES		

• Sealing of building and expansion joints

Not designed to seal immersed joints or below-waterline

• Primer: Prep M for non-porous and metal substrates, Prep P

Sealing in general construction

Sealing most building materials

Sealing tilt slabs

Sealing air seals

for porous substrates

applications

#### Meets N7BC E2/AS1

- BRANZ appraised: Appraisal No.705 (2010)
- ISO 11600/F/25LM compliant
- Fully paintable to DIN 52452, PT4
- Ideal for green buildings
- Suitable for LOSP
- Non slump
- Easy to gun and tool
- Total movement 50%(± 25%)
- Verv low shrinkage
- One component



Auckland PO Box 112191 Penrose 1642 148 Pavilion Drive Auckland Airport, New Zealand (09) 257 5847 Freephone 0508 222 272

Wellington PO Box 35093 Naenae 19 Eastern Hutt Road Wellington, New Zealand (04) 567 5119 Freephone 0508 222 777



bostik.co.nz

