

Technical Data Sheet Blu-Tack

Description

Permanently plastic, reusable multi purpose adhesive. Excellent adhesive qualities. Very Pliable. Non-toxic – safe for all the family.

Classifications/Standards Product and Packaging

Tested in accordance to AS/NZS ISO 8124:2003 (Safety of Toys – Part 3: Migration of certain elements)

Features

- Permanently plastic and pliable
- Reusable
- Australian Made
- Available in strips for ease of use
- Non toxic suitable for all the family



Recommended Uses

Blu-Tack is recommended for use on non-porous surfaces such as vinyl coated wallpapers, painted surfaces, glass, metal etc.

Blu-Tack has a myriad of uses around the home, office, school, factory or workshop.

Number of uses are endless but here are some examples:-

- Hold up posters, cards, children's paintings, certificates, party decorations, maps, messages, etc.
- Holds in place telephones, mouse mats, calculators, ornaments to shelves, photos in albums, screws to screw drivers, holds model parts in position for painting or gluing, and picture frames straight.
- Safely stores pins, keys, screws and other small objects.
- Use in floral arrangements to keep flowers in place.
- Clean fluff from fabric and dirt from computers, model railway tracks or remove dust from hard to get at places.
- Use as a putty to block out breezes.

Application Instructions

Surface Preparation

- 1. Wash hands before use.
- 2. Ensure surfaces are clean; dry free from grease and loose materials.

Application



Blu-Tack

Blu-Tack works because its pressure sensitive:

- 1. For non-laminated surfaces make a 'blob' by tearing off a piece, pull and stretch into a ball and apply to one surface.
- 2. For laminated surfaces cut off 3-5cm pieces of Blu-Tack, remove the release paper on one side, apply to one surface, then remove the other release paper.
- 3. Using good thumb pressure, apply to the other surface.

Removal

To remove Blu-Tack, hold and twist off or roll it carefully off the surface. Any remaining shreds can be removed by rolling or dabbing a blob of Blu-Tack over the surfaces.

Limitations

- Do not use Blu-Tack on absorbent, silk screen printed or hand stencilled wallpaper nor on porous brickwork.
- Care should be taken on painted plaster as Blu-Tack's adhesive qualities may cause paint to come away from wall.

| i i oper eles | | |
|---------------|------------------------|--|
| Colour/s: | Blue/Grey | |
| Specific | Approx 1.9 | |
| Gravity: | | |
| Physical | Putty Strips | |
| Form: | | |
| Chemical | Synthetic Polymer Base | |
| Туре: | | |
| Solids | 100% | |
| Content: | | |
| Solubility: | Insoluble in water | |
| | | |

Properties

Storage & Shelf Life

Store away from heat, strong oxidising agents and acids. Shelf life is 5 years if stored in room/indoor conditions.

Health & Safety

Non harmful. Does not contain latex. For more detailed information refer to Material Safety Data Sheet.

FIRST AID Not expected to cause a problem if swallowed, but if discomfort is experienced, seek medical advice.

In case of emergency, contact 1800 033 111.

PRECAUTION

The adhesive properties of Blu-Tack increase over time, so take extra care when removing after a period of months. On some surfaces after a long period of time Blu-Tack can leave a slight oily mark but this can often be removed using De-Solv-It Sticky Spots, Stain Remover or lighter fluid. Before using these products, we recommend you test on a small inconspicuous area. Not suitable to support heavy objects. 0.5g holds 105g of load.

www.bostik.com.au



Blu-Tack

FIRE Non-flammable.

Packaging

Available in 75 grams in a cardboard envelope, packed in cartons of 10.

Product Details

| Item Number | Size | Colour | Pack Quantity |
|-------------|------|-----------|---------------|
| 371351 | 75g | Blue/Grey | 10 |





Bostik Blu-Tack

www.bostik.com.au

Page 3/3



The information in this Technical Data Sheet is intended for the assistance of purchasers and is of a general nature. It reflects the extent of our knowledge and experience of our products and is based on tests which we believe to be reliable. However, no guarantee of accuracy can be given due to the wide range of surfaces, environmental and field conditions and variations encountered in raw materials, manufacturing equipment and methods at the place where the work is performed. Some of these will be beyond our knowledge or control. We recommend purchasers carry out their own tests to determine the suitability of the product for their particular purposes

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK AUSTRALIA PTY LTD

Head Office

Phone: (03) 9279 9333 Phone Stationery: Bostik Australia Pty Ltd, 51-71 High Street, Thomastown Vic 3074 A.B.N. 79 003 893 838 Fax: (03) 9261 4744 Freecall 1800 898 551

Product Enquiries: stationery.australia@bostik.com



●SAIGLOBAL Quality endorsed ISO9001 (Thomastown site) TS16949 (Automotive). Product: Issue Date: Issue No.: Author: Division: Total Pages: Blu-Tack June 2015 5 David Hitzler Consumer 4

www.bostik.com.au