

**BOSTIK 791 FOAM ADHESIVE Yellow**  
 Revision Number 1.01

Revision Date 24-May-2018  
 Supersedes Date: 01-Jun-2017

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product Identifier

**Product Name** BOSTIK 791 FOAM ADHESIVE Yellow  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Contact adhesives.  
**Uses advised against** No information available.

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik New Zealand Limited  
 19 Eastern Hutt Road Wingate,  
 Lower Hutt, New Zealand  
 Tel: 04-567 5119  
 Fax: 04-567 5412

### 1.4. Emergency telephone number

**Emergency Telephone** 24 Hr: 0800 243 622  
 +64 4 917 9888  
 Poison Centre : 0800 764 766

**E-mail address** SDS.AP@Bostik.com

## Section 2: HAZARD IDENTIFICATION

### 2.1. Classification of the substance or mixture

Aspiration toxicity	Category 1 (6.1E <sup>9</sup> )
Skin Corrosion/Irritation	Category 2 (6.3A)
Serious Eye Damage/Eye Irritation	Category 2 (6.4)
Reproductive toxicity	Category 2 (6.8B)
STOT - Single Exposure	Category 3 (!)
Specific target organ toxicity (repeated exposure)	Category 2 (6.9B)
Acute aquatic toxicity	Category 2 (9.1D)
Chronic aquatic toxicity	Category 2 (9.1B)
Flammable Liquids	Category 2 (3.1B)

Classification in parenthesis is applicable for New Zealand Hazard Classification

**ERMA Group** HSR002662

### 2.2. Label Elements



**Signal Word** DANGER

#### Hazard statements

H304 - May be fatal if swallowed and enters airways

# Safety Data Sheet

**BOSTIK 791 FOAM ADHESIVE Yellow**  
Revision Number 1.01

Revision Date 24-May-2018  
Supersedes Date: 01-Jun-2017

H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H361 - Suspected of damaging fertility or the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure  
H411 - Toxic to aquatic life with long lasting effects  
H225 - Highly flammable liquid and vapor

## Precautionary Statements - Prevention

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P281 - Use personal protective equipment as required  
P264 - Wash face, hands and any exposed skin thoroughly after handling  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment  
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P235 - Keep cool

## Precautionary Statements - Response

P321 - Specific treatment (see supplemental first aid instructions on this label)

### Inhalation

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

### Skin

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P363 - Wash contaminated clothing before reuse

### Eyes

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

### Ingestion

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331 - Do NOT induce vomiting

### Fire

In case of fire: Use CO2, dry chemical, or foam to extinguish

### Spill

P391 - Collect spillage

## Precautionary Statements - Storage

P405 - Store locked up

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

## Precautionary Statements - Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## 2.3. Other Hazards

# Safety Data Sheet

BOSTIK 791 FOAM ADHESIVE Yellow  
Revision Number 1.01

Revision Date 24-May-2018  
Supersedes Date: 01-Jun-2017

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Mixture

### 3.2 Mixtures

Chemical Name	CAS No	Weight-%
Acetone	67-64-1	20- <40
Cyclohexane	110-82-7	10 - <20
Toluene	108-88-3	10 - <20
Methylcyclohexane	108-87-2	5 - <10
Hexane	110-54-3	1 - <5
Tall oil rosin	8052-10-6	0.1- <1
Zinc oxide	1314-13-2	0.1- <1

\*\*\* Any remaining ingredients are not hazardous

## Section 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.
<b>Inhalation</b>	Remove to fresh air. Call a physician. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a physician.
<b>Skin Contact</b>	Wash off immediately with plenty of water. Wash contaminated clothing before reuse. If skin irritation persists, call a physician. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician.
<b>Self-Protection of the First Aider</b>	Remove all sources of ignition. Use personal protective equipment as required.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** None known.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

### 4.4. Reference to Other Sections

**Reference to other sections** See Section 12: ECOLOGICAL INFORMATION. Section 7: HANDLING AND STORAGE. Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

## Section 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Use CO<sub>2</sub>, dry chemical, or foam.

# Safety Data Sheet

BOSTIK 791 FOAM ADHESIVE Yellow  
Revision Number 1.01

Revision Date 24-May-2018  
Supersedes Date: 01-Jun-2017

**Unsuitable Extinguishing Media** No information available.

## 5.2. Special hazards arising from the substance or mixture

**Specific Hazards Arising from the Chemical** Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Extremely flammable.

## 5.3. Advice for firefighters

**Special Protective Equipment for Fire-fighters** Wear self contained breathing apparatus for fire fighting if necessary.

## **Section 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak.

**Other Information** Water spray may reduce vapor; but may not prevent ignition in closed spaces.

**For emergency responders** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

### 6.2. Environmental precautions

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

### 6.3. Methods and material for containment and cleaning up

**Methods for Containment** Dike far ahead of spill; use dry sand to contain the flow of material. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

**Methods for cleaning up** Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

### 6.4. Reference to other sections

**Reference to other sections** See Section 12: ECOLOGICAL INFORMATION  
Section 7: HANDLING AND STORAGE  
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Section 7: HANDLING AND STORAGE**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray.

### 7.2. Conditions for safe storage, including any incompatibilities

**General Hygiene Considerations** When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep

# Safety Data Sheet

**BOSTIK 791 FOAM ADHESIVE Yellow**  
Revision Number 1.01

**Revision Date** 24-May-2018  
**Supersedes Date:** 01-Jun-2017

away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.

**Incompatible Materials** Strong acids and bases Strong oxidizing agents Strong acids Chlorinated compounds

### 7.3. Specific end use(s)

**Other Information** No information available.

### 7.4. References to Other Sections

**Reference to other sections** See Section 12: ECOLOGICAL INFORMATION. Section 7: HANDLING AND STORAGE. Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure Limits

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Chemical Name	New Zealand	Australia	European Union
Acetone 67-64-1	TWA: 500 ppm TWA: 1185 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 2375 mg/m <sup>3</sup>	500 ppm TWA 1185 mg/m <sup>3</sup> TWA 1000 ppm STEL 2375 mg/m <sup>3</sup> STEL	TWA: 500 ppm TWA: 1210 mg/m <sup>3</sup>
Cyclohexane 110-82-7	TWA: 100 ppm TWA: 350 mg/m <sup>3</sup> STEL: 300 ppm STEL: 1050 mg/m <sup>3</sup>	100 ppm TWA 350 mg/m <sup>3</sup> TWA 300 ppm STEL 1050 mg/m <sup>3</sup> STEL	TWA: 200 ppm TWA: 700 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> Skin	50 ppm TWA 191 mg/m <sup>3</sup> TWA 150 ppm STEL 574 mg/m <sup>3</sup> STEL	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100ppm STEL: 384mg/m <sup>3</sup> S*
Methylcyclohexane 108-87-2	TWA: 400 ppm TWA: 1610 mg/m <sup>3</sup>	400 ppm TWA 1610 mg/m <sup>3</sup> TWA	-
Hexane 110-54-3	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>	20 ppm TWA 72 mg/m <sup>3</sup> TWA	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>
Zinc oxide 1314-13-2	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup> TWA 5 mg/m <sup>3</sup> TWA 10 mg/m <sup>3</sup> STEL	-

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>
Cyclohexane 110-82-7	TWA: 100 ppm	IDLH: 1300 ppm TWA: 300 ppm TWA: 1050 mg/m <sup>3</sup>	TWA: 300 ppm TWA: 1050 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 20 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>	TWA: 200 ppm Ceiling: 300 ppm
Methylcyclohexane 108-87-2	TWA: 400 ppm	IDLH: 1200 ppm TWA: 400 ppm TWA: 1600 mg/m <sup>3</sup>	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup>
Hexane 110-54-3	TWA: 50 ppm S*	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m <sup>3</sup>	TWA: 500 ppm TWA: 1800 mg/m <sup>3</sup>
Zinc oxide 1314-13-2	STEL: 10 mg/m <sup>3</sup> respirable particulate matter TWA: 2 mg/m <sup>3</sup> respirable particulate matter	IDLH: 500 mg/m <sup>3</sup> Ceiling: 15 mg/m <sup>3</sup> dust TWA: 5 mg/m <sup>3</sup> dust and fume STEL: 10 mg/m <sup>3</sup> fume	TWA: 5 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction

# Safety Data Sheet

BOSTIK 791 FOAM ADHESIVE Yellow  
Revision Number 1.01

Revision Date 24-May-2018  
Supersedes Date: 01-Jun-2017

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available

OTHER INFORMATION No information available

## 8.2. Exposure controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

## PPE - Personal Protection Equipment

Eye/Face Protection	Wear safety glasses with side shields (or goggles).
Skin and Body Protection	Wear suitable protective clothing. No special technical protective measures are necessary under normal conditions.
Hand Protection	Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.
Respiratory Protection	No protective equipment is needed under normal use conditions. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of professional filter is recommended.
General Hygiene Considerations	Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and wash before reuse.

Environmental Exposure Controls Do not allow into any sewer, on the ground or into any body of water.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Viscosity Liquid Low
Color	Yellow
Odor	Aromatic Solvent
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	approx 50 °C / 122 °F	
Flash Point	approx -22 °C / -7.6 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	Not applicable for liquids
Flammability Limit in Air		
Upper flammability limit:	8.7	
Lower flammability limit:	1.2	
Vapor Pressure	No information available	
Vapor Density	No information available	
Relative Density	No information available	
Water Solubility	Partially soluble	
Solubility in Other Solvents	No information available	
Partition Coefficient	No information available	
Autoignition Temperature	No information available	
Decomposition Temperature	No information available	
Kinematic Viscosity	No information available	
Dynamic Viscosity	No information available	
Explosive Properties	No information available	
Oxidizing Properties	No information available	

### 9.2. Other information

Softening Point	No information available
Molecular Weight	No information available
Solvent content (%)	No information available
Solid content (%)	approx 13
Density	0.76 g/cm <sup>3</sup>

# Safety Data Sheet

BOSTIK 791 FOAM ADHESIVE Yellow  
Revision Number 1.01

Revision Date 24-May-2018  
Supersedes Date: 01-Jun-2017

Bulk Density No information available  
VOC > 300 g/L

## Section 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

Reactivity Stable under recommended storage conditions.

### 10.2. Chemical stability

Stability Stable under recommended storage conditions

### 10.3. Possibility of hazardous reactions

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

### 10.5. Incompatible materials

Incompatible Materials Strong acids and bases. Strong oxidizing agents. Strong acids. Chlorinated compounds.

### 10.6. Hazardous decomposition products

Hazardous decomposition products Carbon oxides.

## Section 11: TOXICOLOGY INFORMATION

### 11.1. Information on toxicological effects

#### Acute Toxicity

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Inhalation No data available.  
Eye contact No data available.  
Skin Contact No data available.  
Ingestion No data available.

#### Numerical measures of toxicity

##### Unknown acute toxicity

2.5999996 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
11.5601796 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
47.6569296 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
56.0919896 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
36.8653596 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg ( Rat )	>15800 mg/Kg (rat)	= 79 mg/l( Rat ) 4 h
Cyclohexane 110-82-7	= 12705 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 9500 ppm ( Rat ) 4 h
Toluene 108-88-3	= 5580 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	> 20 mg/L ( Rat ) 4 h
Methylcyclohexane 108-87-2	> 3200 mg/kg ( Rat )	>2920 mg/Kg bw (rat) 24 hour	>23 mg/l (vapour) (Rat- OECD 403)
Hexane 110-54-3	= 25 g/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 48000 ppm ( Rat ) 4 h

# Safety Data Sheet

**BOSTIK 791 FOAM ADHESIVE Yellow**  
Revision Number 1.01

**Revision Date** 24-May-2018  
**Supersedes Date:** 01-Jun-2017

Tall oil rosin 8052-10-6	= 7600 mg/kg ( Rat )	-	-
Zinc oxide 1314-13-2	> 5000 mg/kg ( Rat )	LD50 >2000 mg/Kg (Rat) (OECD 402)	LC50 (4h) >5.7 mg/l

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin Corrosion/Irritation</b>	No information available.
<b>Serious Eye Damage/Eye Irritation</b>	No information available.
<b>Sensitization</b>	No information available.
<b>Germ Cell Mutagenicity</b>	No information available.
<b>Reproductive Toxicity</b>	Product is or contains a chemical which is a known or suspected reproductive hazard.
<b>STOT - Single Exposure</b>	No information available.
<b>STOT - Repeated Exposure</b>	No information available.
<b>Target Organ Effects</b>	Central nervous system, Eyes, Kidney, Liver, Peripheral Nervous System (PNS), Respiratory system, Skin.
<b>Aspiration hazard</b>	No information available.
<b>Carcinogenicity</b>	No information available.

Chemical Name	IARC	China	Japan
Toluene	Group 3	-	-

**IARC (International Agency for Research on Cancer)** *Group 3 - Not Classifiable as to Carcinogenicity in Humans*

## **Section 12: ECOLOGICAL INFORMATION**

### 12.1. Toxicity

#### **Ecotoxicity**

#### **Product Information**

Toxic to aquatic life with long lasting effects.

#### **Component Information**

Data obtained on the component(s) include

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mg/L (Oncorhynchus mykiss )	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)
Cyclohexane 110-82-7	EC50 72 h > 9.3 mg/L (Pseudokirchnerella subcapitata)	LC50 96 h 23.03 - 42.07 mg/L (Pimephales promelas static) LC50 96 h 48.87 - 68.76 mg/L (Poecilia reticulata static) LC50 96 h 3.96 - 5.18 mg/L (Pimephales promelas flow-through) LC50 96 h 24.99 - 44.69 mg/L (Lepomis macrochirus static)	EC50 24 h > 400 mg/L (Daphnia magna )
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 48 h 5.46 - 9.83 mg/L (Daphnia magna Static) EC50 48 h = 11.5 mg/L (Daphnia magna )
Methylcyclohexane 108-87-2	10 mg/l (Pseudokirchneriella subcapitata - OECD 201)	2.07 mg/l (Oryzias latipes )	3 mg/l (Daphnia magna - OECD 202)
Hexane 110-54-3	-	LC50 96 h 2.1 - 2.98 mg/L (Pimephales promelas flow-through)	EC50 24 h > 1000 mg/L (Daphnia magna )
Tall oil rosin 8052-10-6	EC50 72 h 185 - 217 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 100 - 200 mg/L (Brachydanio rerio static)	EC50 48 h 238 - 479 mg/L (Daphnia magna )
Zinc oxide 1314-13-2	LC 50 (72Hr) 0.136 mg/L	LC50 (96h) =0.7 mg/L Fish (Danio rerio)	LC 50 (48Hr) =0.5 mg/l (Ceriodaphnia dubia)

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential



# Safety Data Sheet

BOSTIK 791 FOAM ADHESIVE Yellow  
Revision Number 1.01

Revision Date 24-May-2018  
Supersedes Date: 01-Jun-2017

No information available.

## 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

## 12.6. Other adverse effects

No information available.

**Endocrine Disruptor  
Information**

## **Section 13: DISPOSAL CONSIDERATIONS**

### 13.1. Waste treatment methods

**Waste from Residues/Unused Products** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging** Improper disposal or reuse of this container may be dangerous and illegal.

## **Section 14: TRANSPORTATION INFORMATION**

### IMDG

UN Number	UN1133
Proper Shipping Name	Adhesives
Transport hazard class(es)	3
Packing Group	II
EmS-No	F-E, S-D
Limited Quantity (LQ)	5 L
Description	UN1133, Adhesives, 3, II, (-22°C c.c.)

### IATA

UN/ID No	UN1133
Proper Shipping Name	Adhesives
Transport hazard class(es)	3
Packing Group	II
ERG Code	3L
Limited Quantity (LQ)	1 L
Special Provisions	A3
Description	UN1133, Adhesives, 3, II

### ADR

UN/ID No	UN1133
Proper Shipping Name	Adhesives, Environmentally Hazardous
Transport hazard class(es)	3
Labels	3
Packing Group	II
Description	UN1133, Adhesives, Environmentally Hazardous, 3, II, (D/E)
Environmental Hazard	Yes
Limited Quantity (LQ)	5 L
Special Provisions	640C
Classification Code	F1
Tunnel Restriction Code	(D/E)

## **Section 15: REGULATORY INFORMATION**

### National Regulations

# Safety Data Sheet

**BOSTIK 791 FOAM ADHESIVE Yellow**  
Revision Number 1.01

**Revision Date** 24-May-2018  
**Supersedes Date:** 01-Jun-2017

## Section 16: OTHER INFORMATION

### Key or legend to abbreviations and acronyms used in the safety data sheet

No information available

### Key Literature References and Sources for Data

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision Date** 24-May-2018

**Revision Note** Not applicable.

**Training Advice** Provide adequate information, instruction, and training for operator

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**