

ASA FLEX COLOURED SILICONE CHARCOAL

Revision Number 1

Revision date 04-Aug-2019 Supersedes Date: 04-Aug-2019

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product NameASA FLEX COLOURED SILICONE CHARCOALPure substance/mixtureMixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Sealant.
Uses advised against	No information available.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik New Zealand Limited 19 Eastern Hutt Road Wingate, Lower Hutt, New Zealand Tel: 04-567 5119 Fax: 04-567 5412

1.4. Emergency telephone number

Emergency Telephone	24 Hr: 0800 243 622 +64 4 917 9888
	Poison Centre : 0800 764 766

E-mail address

SDS.AP@Bostik.com

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Acute toxicity - Oral	Category 4 (6.1D)
Acute toxicity - Dermal	Category 4 (6.1D)
Serious eye damage/eye irritation	Category 2A (6.4A)
Skin sensitization	Category 1B
Carcinogenicity	Category 2 (6.7B)

2.2. Label Elements



Signal word

Warning

Hazard statements

H319 - Causes serious eye irritation

H312 - Harmful in contact with skin

H302 - Harmful if swallowed

H351 - Suspected of causing cancer

H317 - May cause an allergic skin reaction

Prevention

ASA FLEX COLOURED SILICONE CHARCOAL

Revision Number 1

Revision date 04-Aug-2019 **Supersedes Date:** No information available

P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P281 - Use personal protective equipment as required P264 - Wash face, hands and any exposed skin thoroughly after handling P270 - Do not eat, drink or smoke when using this product P261 - Avoid breathing dust/fume/gas/mist/vapors/spray P272 - Contaminated work clothing should not be allowed out of the workplace P280 - Wear protective gloves Skin P302 + P352 - IF ON SKIN: Wash with plenty of soap and water P312 - Call a POISON CENTER or doctor/physician if you feel unwell P363 - Wash contaminated clothing before reuse P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention Eyes P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P337 + P313 - If eye irritation persists: Get medical advice/attention Indestion P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell P330 - Rinse mouth Storage P405 - Store locked up Disposal P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other Hazards

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical name	CAS No.	Weight-%
2-Butanone, oxime	96-29-7	1 - <3
2-Butanone, O,O',O"-(methylsilylidyne)trioxime	22984-54-9	1 - <3
N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine	1760-24-3	0.1- <1

*** Any remaining ingredients are not hazardous

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation	Remove to fresh air.	
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.	
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.	
Ingestion	Clean mouth with water and drink afterwards plenty of water.	
Self-protection of the first aider	Use personal protective equipment as required	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms	None known.	
4.3. Indication of any immediate medical attention and special treatment needed		

ASA FLEX COLOURED SILICONE CHARCOAL

Revision Number 1

Note to physicians	Treat symptomatically.	
4.4. Reference to Other Sections		
Reference to other sections	Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Section 11: TOXICOLOGY INFORMATION.	
Section 5: FIRE-FIGHTING MEASURES		

5.1. Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the Keep product and empty container away from heat and sources of ignition. **chemical**

5.3. Advice for firefighters

Special protective equipment for Wear self-contained breathing apparatus and protective suit. **fire-fighters**

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation, especially in confined areas.		
6.2. Environmental precautions			
Environmental precautions	See Section 12 for additional Ecological Information.		
6.3. Methods and material for containment and cleaning up			
Methods for containment	Prevent further leakage or spillage if safe to do so.		
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.		
6.4. Reference to other sections			
Reference to other sections	Section 7: HANDLING AND STORAGE Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION Section 13: DISPOSAL CONSIDERATIONS		

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling			
Advice on safe handling	Ensure adequate ventilation, especially in confined areas.		
7.2. Conditions for safe storage, including any incompatibilities			
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.		
Storage Conditions	Keep container tightly closed and dry. Product cures with moisture.		
Incompatible materials	No information available		

ASA FLEX COLOURED SILICONE CHARCOAL Revision Number 1

7.3. Specific end use(s)			
Specific Use(s)	Sealant.		
Other information	No information available.		
7.4. References to Other Sections			
Reference to other sections	Section 13: DISPOSAL CONSIDERATIONS. Section 10: STABILITY AND REACTIVITY.		
Section 8: EXPOSURE CONT	TROLS/PERSONAL PROTECTION		
8.1. Control parameters			
Exposure Limits This product, as supplied, does not co region specific regulatory bodies	ontain any hazardous materials with occupational exposure limits established by the		
Derived No Effect Level (DNEL)	No information available		
Predicted No Effect Concentration (PNEC)	No information available		
OTHER INFORMATION	No information available		
8.2. Exposure controls			
Engineering controls	Ensure adequate ventilation, especially in confined areas.		
PPE - Personal Protection Equipme	ent		
Eye/face protection Skin and body protection	Wear safety glasses with side shields (or goggles). Wear suitable protective clothing. No special technical protective measures are necessary under normal conditions.		
Hand protection	Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.		
Respiratory protection	No protective equipment is needed under normal use conditions. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask,		

or for short periods of work, a combination of professional filter is recommended. **General hygiene considerations**Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and wash before reuse.

Environmental exposure controls No information available.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Color Odor Odor threshold

Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Thixotropic Paste Off-white Characteristic No information available

Values No data available Remarks • Method

ASA FLEX COLOURED SILICONE CHARCOAL Revision Number 1

Revision date 04-Aug-2019 Supersedes Date: No information available

Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits		
Vapor pressure	No data available	
Vapor density	No data available	
Relative density	No data available	
Water solubility	No data available	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No information available	
Oxidizing properties	No information available	
9.2. Other information		
Softening Point	No information available	
Molecular weight	No information available	
Solvent content (%)	No information available	
Solid content (%)	No information available	
Density		No information available
Bulk density	No information available	
VOC Content (%)	No information available	
Section 10: STABILITY AND	REACTIVITY	
OCCUPITIO. STABILITT AND		

10.1. Reactivity

Reactivity

None under normal use conditions.

10.2. Chemical stability

10.3.	Possibility	of	hazardous	reactions
-------	-------------	----	-----------	-----------

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Product cures with moisture.

10.5. Incompatible materials

Incompatible materials No information available.

10.6. Hazardous decomposition products

Hazardous decomposition None under normal use conditions.

products

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Acute Toxicity

Product Information

Product does not present an acute toxicity hazard based on known or supplied information.

ASA FLEX COLOURED SILICONE CHARCOAL Revision Number 1

Revision date 04-Aug-2019 **Supersedes Date:** No information available

Inhalation Eye contact	No data available. No data available.
Skin contact Ingestion	No data available. No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butanone, oxime 96-29-7	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat)4 h
2-Butanone, O,O',O''-(methylsilylidyne)trioxime 22984-54-9	LD50 = 2463 mg/Kg (Rat) (OECD 401)	LD50 >2000 mg/Kg (Rat) (OECD guideline 402)	-
N-[3-(Trimethoxysilyl)propyl]-1,2-et hanediamine 1760-24-3	= 2295 mg/kg (Rat)	>2000 mg/Kg (Rat)	LC50 4H (Aerosol)1.5 - 2.44 mg/L air

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Sensitization	No information available.
Germ cell mutagenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Target organ effects	No information available.
Aspiration hazard	No information available.
Carcinogenicity	The following substance(s) are classified in Annex VI CLP (1272/2008) as carcinogenic.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity

Product Information None known.

Component Information

Data obtained on the component(s) include

Chemical name	Algae/aquatic plants	Fish	Crustacea
2-Butanone, oxime	EC50: =83mg/L (72h,	LC50: =760mg/L (96h, Poecilia	EC50: =750mg/L (48h, Daphnia
96-29-7	Desmodesmus subspicatus)	reticulata) LC50: 777 - 914mg/L	magna)
		(96h, Pimephales promelas) LC50:	
		320 - 1000mg/L (96h, Leuciscus	
		idus)	
2-Butanone,	EC50 (72h) = 94 mg/L	EC50 (96h) >120 mg/L Fish	EC50 (48h) > 120 mg/L (Daphnia
O,O',O''-(methylsilylidyne)trioxime	(Pseudokirchneriella subcapitata)	(Oncorhynchus mykiss)Freshwater	magna) OECD 202
22984-54-9	OECD 201	static	
		(OECD guideline 203)	
N-[3-(Trimethoxysilyl)propyl]-1,2-et	-	LC50 (96H) =597 mg/L Fish (Danio	EC50 (48h) =81mg/L Daphnia
hanediamine		rerio)Semi-static	magna Static
1760-24-3			-

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

ASA FLEX COLOURED SILICONE CHARCOAL

Revision Number 1

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
2-Butanone, oxime 96-29-7	0.65	5.8
2-Butanone, O,O',O''-(methylsilylidyne)trioxime 22984-54-9	1.69	5.2
N-[3-(Trimethoxysilyl)propyl]-1,2-ethanedi amine 1760-24-3	-0.3	-

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment
2-Butanone, oxime	The substance is not PBT / vPvB
96-29-7	
2-Butanone, O,O',O''-(methylsilylidyne)trioxime	The substance is not PBT / vPvB
22984-54-9	
N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine	The substance is not PBT / vPvB
1760-24-3	

12.6. Other adverse effects

No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues/unused products	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14: TRANSPORT INFORMATION

IMDG	Not regulated
ΙΑΤΑ	Not regulated
ADR	Not regulated

Section 15: REGULATORY INFORMATION

National Regulations

ERMA Group

HSR002679

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet No information available

Key Literature References and Sources for Data

ASA FLEX COLOURED SILICONE CHARCOAL Revision Number 1

Prepared By	Product Safety & Regulatory Affairs
Revision date	04-Aug-2019
Revision note	Not applicable.
Training Advice	No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet