

1 IDENTIFICATION OF THE PRODUCT AND OF THE SUPPLIER

Product Name Superfixall Grey

Hazard Statement Classified as Hazardous according to HSNO in New Zealand.

Not classified as a Dangerous Good according to NZS5433:1999

Transport of Dangerous Goods on Land.

Recommended Use Cement based tile adhesive. Superfixall Grey powder is mixed with

water to make a trowellable paste.

Supplier Bostik New Zealand Limited

Street Address 19 Eastern Hutt Road, Wingate, Lower Hutt, New Zealand

 Telephone
 ++64 4 567 5119

 Facsimile
 ++64 4 567 5412

 Website
 www.bostik.co.nz

Emergency Telephone Number National Poisons Centre

0800 POISON or 0800 764 766

Emergency Response In New Zealand 0800 CHEMCALL or 0800 243 622

In Australia 1800 033 111
Globally ++64 3 353 0199

2 HAZARDS IDENTIFICATION

Hazard Statement DANGER Causes severe eye damage.

Precautions Do not breathe dust. Wear a dust mask when handling powder. Wear

protective gloves and safety glasses at all times. Do not handle until safety

precautions have been read and understood.

This product contains small amounts of crystalline silica, of which some will be respirable (primarily respirable quartz). **Prolonged** or **repeated** inhalation of respirable quartz from this product may cause silicosis, a seriously disabling and fatal lung disease.

HSNO Classifications

6.3A Causes skin irritation

6.4A Causes severe eye irritation8.3A Causes serious eye damage

Superfixall Grey

Issued: 19/05/2016 Version: 1 Page 1 of 7



3 **COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	CAS	Proportion
Cement	65997-15-1	30 – 50%
Sand (containing respirable quartz)	14808-60-7	40 – 70 %
Non-hazardous materials	-	To 100%

FIRST AID MEASURES

If poisoning occurs, contact the National Poison Centre (New Zealand 0800 POISON or 0800 764 766).

First Aid

Inhalation Remove person to fresh air. Remove contaminated clothing. Get

medical advice if effects persist.

Skin Contact Remove contaminated clothing and wash skin with water. Do not scrub.

Irritation is unlikely if skin is washed promptly. If irritation occurs get

medical assistance.

Eye Contact Immediately hold open and flood gently with water for at least 15

minutes. Eyelids to be held open. Remove contact lenses if present

and easy to do. Get medical advice.

Ingestion Rinse mouth with water and give patient water to drink. Get medical

advice immediately. Do NOT induce vomiting because of risk of

aspiration. Never give anything by the mouth to an unconscious patient.

Advice to Physician Treat symptomatically. Can cause corneal burns.

5 **FIRE FIGHTING MEASURES**

Clear fire area of all non-emergency personnel.

Type of Hazard Non-combustible material.

HAZCHEM Code Not applicable.

Fire Hazard Properties Product will not support combustion.

Issued: 19/05/2016 Version: 1 Page 2 of 7



6 ACCIDENTAL RELEASE MEASURES

Small Spills <20 litres

Clean up immediately. Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of dust. Sweep or vacuum up, but avoid generating dust. Scrape up wet mixed paste and wash area well with water. Refer to disposal section of this SDS.

Large Spills >20 litres

Clean up immediately. Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of dust by wearing a dust mask. Contain spill to prevent run off into drains and waterways. Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal or recycling. Ensure thorough collection of powder. If washing down the spill area, ensure washings are well diluted when discharging to waste. See Disposal section of this SDS for further details.

7 HANDLING AND STORAGE

Handling Avoid breathing dust or contact with material. Wear the appropriate personal

protection equipment as specified in this SDS to prevent eye and skin contact, and

the inhalation of any dust. Wash contaminated skin promptly.

Storage Store in a cool, dry place. Store away from any incompatible materials as defined

in Section 10 of this SDS. Keep containers and bags closed when not in use.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace Exposure Guidelines

Substance	WES-TWA	WES-STEL
Cement	10 mg/m ³	-
Sand – respirable quartz	0.2 mg/m ³	-
Sand (particulates, not otherwise specified)		-
- Total dust	10 mg/m ³	-
 Respirable dust 	3 mg/m ³	-

Engineering Controls Not required in normal use.

Personal Protection Equipment

Avoid dust inhalation. Wear a dust mask if inhalation is likely during mixing. Avoid skin contact especially repeated and prolonged skin contact for both dry powder and mixed paste. Wear gloves, overalls or similar protective clothing, and enclosed footwear. Avoid eye contact. Wear safety glasses during mixing. Wash contaminated clothing before storing or reuse.



9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance Grey powder

Odour Nil

Bulk Density Approximately 1.5

pH (mixed with water, slurry) 12 - 13

Solubility in Water Slightly soluble

10 STABILITY AND REACTIVITY

Stability of Substance This material is stable when stored and used as directed.

Conditions to AvoidDo not store in damp conditions, as product will start to cure and go

hard.

Incompatible Materials No information available.

Hazardous Decomposition

Products

No information available.

Hazardous Reactions No information available.

11 TOXICOLOGICAL INFORMATION

Information given in this Safety Data Sheet is based on the data on the components and the toxicology of similar products.

No adverse health effects are expected if the product is handled in accordance with this SDS and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Oral Toxicity Not toxic, however swallowing can result in irritation to the mouth &

digestive tract, and can cause nausea & vomiting.

Acute Dermal Toxicity Not toxic.

Acute Inhalation Toxicity Not toxic, however is an irritant to mucous membranes and

respiratory tract. Pre-existing upper respiratory and lung diseases

may be aggravated by inhalation of dust.

Skin Irritation Causes severe skin burns.

Superfixall Grey

Issued: 19/05/2016 Version: 1 Page 4 of 7



Eye Irritation Causes severe eye damage.

Sensitisation

(Respiratory & Contact)

Not expected to be a sensitiser.

Carcinogenicity This product contains respirable quartz. Prolonged or repeated

inhalation of high doses of respirable quartz may cause cancer or

silicosis, a seriously disabling and fatal lung disease.

Reproductive /

Developmental Toxicity

Not expected to cause damage to fertility or the unborn child.

Mutagenicity Not expected to be mutagenic.

Target Organ Systemic May cause damage to organs through prolonged or repeated

exposure.

12 ECOLOGICAL INFORMATION

Acute Toxicity

Aquatic Strongly alkaline when mixed with water. Avoid discharging

wash water to waterways.

Soil Not ecotoxic in the soil environment.

Terrestrial Vertebrate Not ecotoxic to terrestrial vertebrates.

Terrestrial Invertebrate Not ecotoxic to terrestrial invertebrates.

Persistence and degradability This product will not biodegrade Once this product has cured

and hardened by reaction with environmental moisture, the

product is no longer hazardous.

Bioaccumulation No data available on the product itself, however the individual

components do not bioaccumulate.

Mobility Will combine with water, but not dissolve. Heavier than water.

13 DISPOSAL CONSIDERATIONS

Substance Disposal Do wash product into storm-water drains or local waterways.

Recycle or recover whenever possible. Mix unwanted product with water according to package directions and allow to cure. Cured product may be

disposed to landfill.

Container Disposal Empty bags may be disposed to landfill.

Superfixall Grey

Issued: 19/05/2016 Version: 1 Page 5 of 7



Local Legislation

Disposal should be in accordance with Hazardous Substances (Disposal) Regulations 2001, and with any other applicable regional and national laws and regulations.

14 TRANSPORT INFORMATION

Land Transport

Not classified as Dangerous Goods by the criteria of NZS 5433:1999 Transport of Dangerous Goods on Land for transport by road or rail.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15 REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Environmental Risk Management Authority (ERMA) Group Standard Number:

Construction Products (Subsidiary Hazard) Group Standard 2006: HSR002544

Hazardous Substances and New Organisms Act (HSNO):

The following are trigger quantities for this substance by itself in a place.

Approved Handler Test Certificate Not required

Tracking Not applicable

16 OTHER INFORMATION

SDS Revisions Safety Data Sheets are updated at least every 5 years. Obtain the latest

version by visiting www.bostik.co.nz.

Reason for Issue First Issue

SDS Distribution The information in this document should be made available to all who may

handle this product.

Superfixall Grey

Issued: 19/05/2016 Version: 1 Page 6 of 7



This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of this product, and in particular how to safely handle and use the product in the workplace. Since Bostik New Zealand Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact Bostik New Zealand Limited.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is available upon request.

Key / Legend

itey / Legena	
SDS	Safety Data Sheet
HSNO	Hazardous Substances and New Organisms Act 1996
WES-TWA	The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure.
WES-STEL	The 15 minute average exposure standard. This applies to any 15 minute period in a working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to WES-TWA; both the short-term and time-weighted average exposures apply.

Disclaimer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.