



PLUMBERS PUTTY

NON DRYING WATER RESISTANT PUTTY SEALANT

Date: 17 September 2014

YOUR SMART ADVANTAGES

- Non tacky
- Does not bleed
- Odourless
- Remains flexible
- Water resistance
- Long lasting

USES

- Interior use only
- Sealing solid surfaces

PRODUCT CHARACTERISTICS

Colour	White
Shrinkage	None on non-absorbent surfaces
Paintability	Cannot be painted
Odour	Nil
Staining	Nil
Chemical resistance	Resistant to water, sea water and dilute alkaline solutions. Low resistance to oil and greases. Poor resistance to solvents and acids.

Product code	
250g tub, 10 per carton	30804018
500g tub, 10 per carton	30804019

TYPICAL PERFORMANCE DATA (approx.)

Needle Penetration - Needle penetrometer (50gm weight, 12 seconds residence time)	14.5 - 18mm
Application temperature	5°C to 30°C
Service temperature	-30 to 50°C

DIRECTIONS FOR USE

Read and understand the Material Safety Data Sheet before using this product.

SURFACE PREPARATION

Always ensure that the surfaces to be sealed are dry and free from oil, dirt and grease. Porous surfaces need to be sealed before applying putty. Bostik N49 Primer is recommended to seal concrete.

APPLICATION

Cut off or break off a hand sized portion of putty. Work briefly to soften the putty and apply to substrate. Press firmly into place ensuring a full seal is achieved.

LIMITATIONS

- Plumbers Putty Seal should not be used in joints where movement in excess of 5% is expected.
- Plumbers Putty Seal should not be used in exterior situations exposed to strong sunlight. A skin will form and further hardening and cracking may occur with prolonged exposure.

CLEANING

Scrape clean then use mineral turpentine to remove putty residues. Wash hands using soap and water.

STORAGE AND SHELF LIFE

Store in a cool dry place below 25°C and out of direct sunlight. Shelf life is 2 years from the date of manufacture when stored as directed.

DISPOSAL

Empty containers may be disposed via local landfill. Dispose of according to local authority regulations. Do not dispose of down drains or into local waterways.

PLUMBERS PUTTY

PRECAUTIONS IN USE

Complete details on each of the products mentioned are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that all concerned read the appropriate Safety Data Sheets. Visit www.bostik.co.nz for copies.

Plumbers Putty is not classified as Dangerous Goods or as a Hazardous Substance. The product however, should be used in accordance with good occupational, health and safety practices

For emergency information contact the National Poisons Information Centre, phone 0800 764 766 (0800 POISON) or CHEMCALL, phone 0800 243 622.

BOSTIK HOTLINE

Smart help 0508 222 777



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Sale of the product by Bostik is subject to the Bostik New Zealand Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.co.nz

Technical Advice

Tel: 0508 222 777

nzsales@bostik.com

Bostik New Zealand Ltd, 12 Eastern Parkway, Wiri, Auckland, 0612 Lower Hutia, New Zealand. Tel: 0508 222 777 www.bostik.co.nz