

PVA INDOOR OUTDOOR

TRADESMAN WOODGLUE

7 May 2014

YOUR SMART ADVANTAGES

- D₃ Rated superior water resistance
- Superior heat resistance
- Fast bond
- High strength
- Sandable
- Paintable
- Non toxic

USES

- Wood
- Paper
- Leather
- Cardboard

PRODUCT CHARACTERISTICS	
Colour	White
Viscosity	Thick liquid
Composition	PVA
Application temperature	5 to 30°C
Product codes 500mL bottle 4Kg pail 21Kg Jerry can	30804024 30804519 30804518

TYPICAL PERFORMANCE DATA (approx)	
Application temperature	5 to 30°C
Specification DIN EN204	D ₃ – Interior with frequent short-term exposure to running or condensed water and/or heavy exposure to high humidity. Exterior not exposed to weather

DIRECTIONS FOR USE

Read and understand the Material Safety Data Sheet before using this product.

SURFACE PREPARATION

Ensure all surfaces are clean and dry. Free from all loose paint, dust, grease and release agents. Freshly sanded timber is ideal.

APPLICATION

Apply sufficient adhesive to cover one surface. For larger surfaces spread the adhesive with a brush or spreader.

Bring both surfaces together while the adhesive is still wet or tacky. Apply even pressure to ensure a good bond.

Immediately wipe off excess using a damp cloth.

When bonding soft woods (pine), clamp lightly immediately after bonding for a minimum of 30 minutes.

When bonding hard woods (Rimu), clamp lightly immediately after bonding for a minimum of 1 hour.

Full strength develops in about 24 hours

Allow 7 days for full cross linking and water resistance to develop.

LIMITATIONS

– PVA is not a gap filling adhesive and requires close fitting surfaces

CLEANING

Clean with damp cloth immediately after use.

Wash hands with soap and water.

Dried adhesive is best removed by scraping or sanding.

STORAGE AND SHELF LIFE

Store in a cool dry place below 25°C and out of direct sunlight. Shelf life is 12 months from the date of manufacture when stored as directed.

DISPOSAL

Empty containers may be disposed via local landfill.

If spilt, absorb with clay, sand or earth. Collect and seal in properly labelled metal container. Dispose of according to local authority regulations. Do not dispose of down drains or into local waterways.

PVA INDOOR OUTDOOR

PRECAUTIONS IN USE

Complete details on each of the products mentioned are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that all concerned read the appropriate Safety Data Sheets. Visit www.bostik.co.nz for copies.

PVA Indoor Outdoor is not classified as Dangerous Goods or as a Hazardous Substance. The product however, should be used in accordance with good occupational, health and safety practices. Do not swallow and avoid prolonged or repeated contact with the skin. If contact with the eyes occurs, wash eyes with copious quantities of water and consult a doctor if irritation persists.

For emergency information contact the National Poisons Information Centre, phone o800 764 766 (o800 POISON) or CHEMICALL, phone o800 243 622.



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Sale of the product by Bostik is subject to the Bostik New Zealand Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.co.nz

Technical Advice Tel: 0508 222 777 nzsales@bostik.com

Bostik New Zealand Ltd, 19 Eastern Hutt Rd, Wingate, 5019 Lower Hutt, New Zealand. Tel: +64 4 567 5119 www.bostik.co.nz

Page 2 of 2