



Cleaner E

Product

Simson Cleaner E is a preparation agent, ideally suitable for cleaning and degreasing substrates for bonding or sealing with specific Simson products. Consult technical information leaflet of the particular product.

Applications

- Cleaning and degreasing joints in teakwood decks (prior to the application of Simson Primer P).
- Removing uncured sealant and adhesive, based on Silyl Modified Polymer (SMP), silicones, polysulphide and polyurethane from substrates and tools.
- Degreasing and cleaning glass substrates.

Method of use


The substrates should be firmly rubbed with a clean, colourless cloth, wetted with Cleaner E. In case the substrate is strongly contaminated repeat this once more.

Note: It is recommended to make a trial in advance on a small piece, to check whether the substrate will not be affected by Cleaner E.

Drying time

Pretreatment of teakwood decks: Prep P can be applied immediately.

Other applications: it is recommended to allow a drying time of 5 minutes.



ADHESIVES AND SEALANTS

Cleaner E

Technical data

Dry contents	0%
Specific gravity	0.9 g/ml
Flashpoint	-4°C

Colour
transparent

Packaging
tin 500 ml

Article code
023360

Coverage

The coverage of Cleaner E on teakwood deck joints is approximately 15 m² per liter.

Storage stability

Cleaner E can be stored for 12 months in a closed (unopened) container in a dry place at temperatures between +5°C and +30°C.

Further information

The following publication is available on request:

- Material Safety Data Sheets (MSDS)

Bostik B.V.

Postbus 303
5201 AH 's-Hertogenbosch
Tel: +31 (0)73 6 244 244
Fax: +31 (0)73 6 244 344
E-mail: infonl@bostik.com
Internet: www.bostik.nl

Bostik Belux SA-NV

Meulestedekaai 86
B-9000 Gent
Tel: +32 (0)9 255 17 00
Fax: +32 (0)9 255 17 01
E-mail: info@bostik.be
Internet: www.bostik.be