

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives and/or sealants.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone No information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

2.2. Label Elements

Not classified

Signal word
None

Hazard statements
Not classified

EU Specific Hazard Statements

EUH208 - Contains Dioctyltinbis(acetylacetonate). May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.

2.3. Other Hazards

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2. Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Trimethoxyvinylsilane	220-449-8	2768-02-7	1 - <5	Acute Tox. 4 (H332) Flam. Liq. 3 (H226)		01-2119513215-52-XXXX
1-Propanamine, 3-(trimethoxysilyl)-	237-511-5	13822-56-5	1 - <2.5	Skin Irrit. 2 (H315) Eye Dam. 1 (H318)		01-2119510159-45-XXXX
Diocetyl tinbis(acetylacetonate)	483-270-6	54068-28-9	0.1 - <1	STOT SE 2 (H371) Skin Sens. 1 (H317)	Skin Sens. 1 :: C>=5%	01-0000020199-67-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Call a doctor immediately. Rinse mouth thoroughly with water. Small amounts of toxic methanol are released by hydrolysis.

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

4.2. Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of toxic and corrosive gases/vapours.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

Other information Ventilate the area. Prevent further leakage or spillage if safe to do so.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep/store only in original container. Protect from sunlight. Store in a well-ventilated place. Keep at temperatures between 5 and 35 °C. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Specific Use(s)
Adhesives and/or sealants.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m ³	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	58 mg/m ³	
worker Long term	Dermal	8.3 mg/kg bw/d	
Short term worker	Inhalation	58 mg/m ³	
Short term worker	Dermal	8.3 mg/kg bw/d	

Diocetylbinbis(acetylacetonate) (54068-28-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

Long term Systemic health effects worker	Dermal	0.07 mg/kg bw/d	
Long term Systemic health effects worker	Inhalation	84 mg/m ³	
Short term Systemic health effects worker	Inhalation	84 mg/m ³	
Long term Short term Local health effects worker	Inhalation	0.091 mg/m ³	

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m ³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Microorganisms in sewage treatment	13 mg/l
Soil	0.04 mg/l
Marine water	0.033 mg/l

Diocetylbinbis(acetylacetonate) (54068-28-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	26 µg/l
Marine water	2.6 µg/l
Freshwater - intermittent	260 µg/l
Sewage treatment plant	1 mg/l
Freshwater sediment	0.155 mg/kg dry weight
Marine sediment	0.0155 mg/kg dry weight
Soil	0.0158 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Wear chemical splash goggles and face shield when eye and face contact is possible due to splashing or spraying of material. Eye protection must conform to standard EN 166

Hand protection

Wear suitable gloves. Gloves must conform to standard EN 374. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Wear protective butyl rubber gloves. The breakthrough time for the mentioned glove material is in general

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

	greater than 480 min. Wear protective nitrile rubber gloves. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 180 min.
Skin and body protection	None under normal use conditions.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.
Recommended filter type:	Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	Grey
Odour	No information available
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	> 60	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	No data available	
Water solubility	Immiscible in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature		
Kinematic viscosity	> 21 mm ² /s	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available
VOC Content (%)	No information available
Density	1.45 - 1.51 g/cm ³

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

Stability Stable under normal conditions.

Explosion data
Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact The test item induced a mean In-vitro irritancy score ≤ 3 , the test item was considered as a test chemical not requiring classification for eye irritation or serious eye damage (UN GHS No Category).

Skin contact Causes mild skin irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 4,059.20 mg/kg
ATEmix (inhalation-vapour) 559.38 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane 2768-02-7	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3360 μ L/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
1-Propanamine,	LD50 (Rattus) > 2000 mg/ kg	LD50 (Oryctolagus cuniculus)	

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

3-(trimethoxysilyl)- 13822-56-5	(2,97 ml/kg) (OECD 401)	> 2000 mg/kg 11,3 ml/kg OECD 402	
Diocetylbinbis(acetylacetonate) 54068-28-9	LD50 =2500 mg/kg (Rattus)	LD50 >2000 mg/kg (Rattus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		72 hours	irritant

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Component Information				
Trimethoxyvinylsilane (2768-02-7)				
Method	Species	Exposure route	Results	
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser	

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Did not cause sensitisation on laboratory animals

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Component Information

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)		
Method	Species	Results
OECD Test No. 408: Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	Not Classifiable

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	EC50 (72h) > 1000 mg/l (Desmodesmus subspicatus) EU Method C.3 (Algal Inhibition test)	LC50 (96h) > >934 mg/L (Danio rerio) OECD 203	-	EC50 (48h) = 331 mg/L (Daphnia magna) OECD 202		
Diocetyl tinbis(acetylacetonate) 54068-28-9	-	LC50 (96h) =86 mg/L (Static)	-	EC50 (48h) =58.6 mg/L (Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information			
Trimethoxyvinylsilane (2768-02-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable
1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)			
Method	Exposure time	Value	Results
OECD Test No. 301A: Ready	28 days		Not readily biodegradable 67

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

Biodegradability: DOC Die-Away Test (TG 301 A)			%
--	--	--	---

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Trimethoxyvinylsilane 2768-02-7	1.1	-

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment This preparation contains no substance considered to be persistent, bio-accumulating nor toxic (PBT) .

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane 2768-02-7	The substance is not PBT / vPvB
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	The substance is not PBT / vPvB
Dioctyltinbis(acetylacetonate) 54068-28-9	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supercedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

14.6 Special Provisions None

IMDG

14.1 UN number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Marine pollutant Np
14.6 Special Provisions None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Germany

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

Ordinance on Industrial Safety and Health - Germany - BetrSichV
No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

MAL-Code 0-1

Sweden

Occupational exposure limits AFS 2018:1

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H332 - Harmful if inhaled
H371 - May cause damage to organs

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 25-Jun-2020

Indication of changes

Revision note SDS sections updated, 1, 2, 3, 8, 11, 12, 15.

Training Advice No information available

Further information No information available

SAFETY DATA SHEET

BOSTIK H750 SEAL'N'BOND PREMIUM GREY
Supersedes Date: 28-Jun-2020

Revision date 25-Jun-2020
Revision Number 1

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet