

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supersedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name
Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone No information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

2.2. Label Elements

Not classified

Signal word
None

Hazard statements
Not classified

EU Specific Hazard Statements

EUH208 - Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.

2.3. Other Hazards

SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supersedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

The product contains no substances which at their given concentration, are considered to be hazardous to health

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Trimethoxyvinylsilane	220-449-8	2768-02-7	1 - <3	Acute Tox. 4 (H332) Flam. Liq. 3 (H226)		01-2119513215-52-XXXX
N-(3-(trimethoxysilyl)propyl)ethylenediamine	217-164-6	1760-24-3	0.1- <1	Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H332) STOT SE 3 (H335)		01-2119970215-39-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Call a doctor immediately. If swallowed, rinse mouth with water (only if the person is

SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supersedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

conscious). Small amounts of toxic methanol are released by hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

Other information Ventilate the area. Prevent further leakage or spillage if safe to do so.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supersedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep at temperatures between 5 and 35 °C. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Specific Use(s)
Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m ³	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	35.5 mg/m ³	
worker Systemic health effects Long term	Dermal	5 mg/kg bw/d	

Derived No Effect Level (DNEL)

SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supersedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m ³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Oral	2.5 mg/kg bw/d	
Consumer Systemic health effects Long term	Inhalation	8.7 mg/m ³	
Consumer Systemic health effects Long term	Dermal	2.5 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.0062 mg/l
Sewage treatment plant	25 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166
- Hand protection** Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
- Skin and body protection** None under normal use conditions.
- Respiratory protection** In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
- Recommended filter type:** Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supersedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	Dark Grey
Odour	Characteristic
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	> 100 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	No data available	
Water solubility	Product cures with moisture	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature		
Kinematic viscosity	> 21 mm ² /s	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available
VOC Content (%)	No information available
Density	1.45 g/cm ³

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Product cures with moisture.
------------	------------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None under normal processing.
------------------------------------	-------------------------------

SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supersedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

10.4. Conditions to avoid

Conditions to avoid Protect from moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.
Eye contact Based on available data, the classification criteria are not met.
Skin contact Based on available data, the classification criteria are not met.
Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 9,863.20 mg/kg
ATEmix (inhalation-vapour) 557.10 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane 2768-02-7	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3360 µL/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44 mg/L air

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supersedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit				Mild skin irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal			Not a skin sensitiser

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal			sensitising

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro				Not mutagenic

Carcinogenicity Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat				Not Classifiable

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supersedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) = 597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) = 81mg/L Daphnia magna Static		

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Trimethoxyvinylsilane 2768-02-7	1.1	-
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-0.3	-

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane 2768-02-7	The substance is not PBT / vPvB
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	The substance is not PBT / vPvB

SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supercedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

IMDG

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	Np
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supersedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

MAL-Code 0-1

Sweden

Occupational exposure limits AFS 2018:1

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL DARK GREY
Supersedes Date: 18-Aug-2020

Revision Date: 18-Aug-2020
Revision Number 1

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H332 - Harmful if inhaled
H335 - May cause respiratory irritation

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date: 18-Aug-2020

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet