

**BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY**  
Supersedes Date: 19-Aug-2020

Revision Date: 19-Aug-2020  
Revision Number 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product Identifier

**Product Name** BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant.  
**Uses advised against** None known.

### 1.3. Details of the supplier of the safety data sheet

**Company Name**  
Bostik SA  
420 rue d'Estienne d'Orves  
92700 Colombes  
FRANCE  
Tel: +33 (0)1 49 00 90 00

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**Emergency Telephone** No information available

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

### 2.2. Label Elements

Not classified

**Signal word**  
None

**Hazard statements**  
Not classified

#### EU Specific Hazard Statements

EUH208 - Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.  
EUH210 - Safety data sheet available on request.

#### Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.

### 2.3. Other Hazards

# SAFETY DATA SHEET

**BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY**  
Supersedes Date: 19-Aug-2020

Revision Date: 19-Aug-2020  
Revision Number 1

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Trimethoxyvinylsilane	220-449-8	2768-02-7	1 - <3	Acute Tox. 4 (H332) Flam. Liq. 3 (H226)		01-2119513215-52-XXXX
N-(3-(trimethoxysilyl)propyl)ethylenediamine	217-164-6	1760-24-3	0.1- <1	Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H332) STOT SE 3 (H335)		01-2119970215-39-XXXX

### Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Call a doctor immediately. If swallowed, rinse mouth with water (only if the person is conscious). Small amounts of toxic methanol are released by hydrolysis.

# SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY  
Supercedes Date: 19-Aug-2020

Revision Date: 19-Aug-2020  
Revision Number 1

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

## 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon dioxide (CO<sub>2</sub>).

### 5.3. Advice for firefighters

Special protective equipment for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

Other information Ventilate the area. Prevent further leakage or spillage if safe to do so.

For emergency responders Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

### 6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

# SAFETY DATA SHEET

**BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY**  
Supersedes Date: 19-Aug-2020

Revision Date: 19-Aug-2020  
Revision Number 1

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep at temperatures between 5 and 35 °C. Keep away from food, drink and animal feedingstuffs.

## 7.3. Specific end use(s)

**Specific Use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

**Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.**

Chemical name	European Union
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> *

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m <sup>3</sup>	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	35.5 mg/m <sup>3</sup>	
worker Systemic health effects Long term	Dermal	5 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level	Safety factor

# SAFETY DATA SHEET

**BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY**  
**Supersedes Date:** 19-Aug-2020

**Revision Date:** 19-Aug-2020  
**Revision Number** 1

		(DNEL)	
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m <sup>3</sup>	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Oral	2.5 mg/kg bw/d	
Consumer Systemic health effects Long term	Inhalation	8.7 mg/m <sup>3</sup>	
Consumer Systemic health effects Long term	Dermal	2.5 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>Trimethoxyvinylsilane (2768-02-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.0062 mg/l
Sewage treatment plant	25 mg/l

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal Protective Equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166
- Hand protection** Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
- Skin and body protection** None under normal use conditions.
- Respiratory protection** In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
- Recommended filter type:** Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

# SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY  
Supersedes Date: 19-Aug-2020

Revision Date: 19-Aug-2020  
Revision Number 1

## 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	Grey
Odour	Characteristic
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	> 100 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	No data available	
Water solubility	Product cures with moisture	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature		
Kinematic viscosity	> 21 mm <sup>2</sup> /s	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

## 9.2. Other information

Solid content (%)	No information available
VOC Content (%)	No information available
Density	1.45 g/cm <sup>3</sup>

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Reactivity	Product cures with moisture.
------------	------------------------------

### 10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

#### Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None under normal processing.
------------------------------------	-------------------------------

### 10.4. Conditions to avoid

Conditions to avoid	Protect from moisture.
---------------------	------------------------

# SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY  
Supersedes Date: 19-Aug-2020

Revision Date: 19-Aug-2020  
Revision Number 1

## 10.5. Incompatible materials

Incompatible materials None known based on information supplied.

## 10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

##### Product Information

**Inhalation** Based on available data, the classification criteria are not met.  
**Eye contact** Based on available data, the classification criteria are not met.  
**Skin contact** Based on available data, the classification criteria are not met.  
**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

#### Numerical measures of toxicity

##### Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 9,383.50 mg/kg  
ATEmix (inhalation-vapour) 559.10 mg/l

##### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane 2768-02-7	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3360 µL/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44 mg/L air

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit				Mild skin irritant

# SAFETY DATA SHEET

**BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY**  
**Supersedes Date:** 19-Aug-2020

**Revision Date:** 19-Aug-2020  
**Revision Number** 1

Acute Dermal Irritation/Corrosion					
-----------------------------------	--	--	--	--	--

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

Component Information			
Trimethoxyvinylsilane (2768-02-7)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	sensitising

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

**Carcinogenicity** Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.



# SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY  
Supersedes Date: 19-Aug-2020

Revision Date: 19-Aug-2020  
Revision Number 1

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) = 597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) = 81mg/L Daphnia magna Static		

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

#### Component Information

##### Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

### 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

#### Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Trimethoxyvinylsilane 2768-02-7	1.1	-
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-0.3	-

### 12.4. Mobility in soil

**Mobility in soil** No information available.

### 12.5. Results of PBT and vPvB assessment

#### PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane 2768-02-7	The substance is not PBT / vPvB
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	The substance is not PBT / vPvB

### 12.6. Other adverse effects

**Other adverse effects** No information available.

# SAFETY DATA SHEET

BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY  
Supersedes Date: 19-Aug-2020

Revision Date: 19-Aug-2020  
Revision Number 1

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
<b>Contaminated packaging</b>	Handle contaminated packages in the same way as the product itself.
<b>European Waste Catalogue</b>	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

### IMDG

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	Np
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

# SAFETY DATA SHEET

**BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY**  
**Supersedes Date:** 19-Aug-2020

**Revision Date:** 19-Aug-2020  
**Revision Number** 1

## **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

## **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

## **Persistent Organic Pollutants**

Not applicable

## **National regulations**

### **France**

### **Germany**

#### **Ordinance on Industrial Safety and Health - Germany - BetrSichV**

No flammable liquids in accordance with BetrSichV

**Water hazard class (WGK)** slightly hazardous to water (WGK 1)

### **Netherlands**

#### **List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)**

Not Listed

**MAL-Code** 0-1

### **Sweden**

Occupational exposure limits AFS 2018:1

## **15.2. Chemical safety assessment**

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### **Key or legend to abbreviations and acronyms used in the safety data sheet**

#### **Full text of H-Statements referred to under section 3**

H226 - Flammable liquid and vapour

H317 - May cause an allergic skin reaction

# SAFETY DATA SHEET

**BOSTIK H760 SEAL'N'FLEX PRO SEAL GREY**  
**Supersedes Date:** 19-Aug-2020

**Revision Date:** 19-Aug-2020  
**Revision Number** 1

---

H318 - Causes serious eye damage  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation

## Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision Date:** 19-Aug-2020

## Indication of changes

**Revision note** Not applicable.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**