

BOSTIK GLASIL OFF WHITE
Supersedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK GLASIL OFF WHITE
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name
Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone No information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

2.2. Label Elements

Not classified

Signal word
None

Hazard statements
Not classified

EU Specific Hazard Statements

EUH208 - Contains Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine. May produce an allergic reaction
EUH210 - Safety data sheet available on request

2.3. Other Hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

PBT and vPvB assessment

SAFETY DATA SHEET

BOSTIK GLASIL OFF WHITE
Supersedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Silane, ethenyltrimethoxy-	220-449-8	2768-02-7	1 - <2.5	Acute Tox. 4 (H332) Flam. Liq. 3 (H226)		01-2119513215-52-XXXX
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	309-629-8	100545-48-0	0.1- <1	Skin Sens. 1 (H317) Aquatic Chronic 3 (H412)	Skin Sens. 1 :: C \geq 25%	01-2119979085-27-XXXX

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration \geq 0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Call a doctor immediately. If swallowed, rinse mouth with water (only if the person is conscious). Small amounts of toxic methanol are released by hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Treat symptomatically.

SAFETY DATA SHEET

BOSTIK GLASIL OFF WHITE
Supercedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

Other information Ventilate the area. Prevent further leakage or spillage if safe to do so.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep at temperatures between 5 and 35 °C. Keep away from food, drink and animal feedingstuffs.

SAFETY DATA SHEET

BOSTIK GLASIL OFF WHITE
Supersedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

7.3. Specific end use(s)

Specific Use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)	
Silane, ethenyltrimethoxy- (2768-02-7)	
Type	worker Systemic health effects Long term
Exposure route	Inhalation
Derived No Effect Level (DNEL)	27,6 mg/m ³

Type	worker Systemic health effects Long term
Exposure route	Dermal
Derived No Effect Level (DNEL)	3,9 mg/kg bw/d

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)	
Type	worker Long term Local health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	3.35 mg/m ³

Derived No Effect Level (DNEL)	
Silane, ethenyltrimethoxy- (2768-02-7)	
Type	Consumer Systemic health effects Long term
Exposure route	Inhalation
Derived No Effect Level (DNEL)	18,9 mg/m ³

Type	Consumer Systemic health effects Long term
Exposure route	Dermal
Derived No Effect Level (DNEL)	7,8 mg/kg bw/d

Type	Consumer Systemic health effects Long term
Exposure route	Oral
Derived No Effect Level (DNEL)	0,3 mg/kg bw/d

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)	
Type	Consumer Long term

SAFETY DATA SHEET

BOSTIK GLASIL OFF WHITE
Supersedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.83 mg/m ³

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Silane, ethenyltrimethoxy- (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166
Hand protection	Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Paste
Colour	Off-white
Odour	Slight Characteristic
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	Not applicable
Melting point / freezing point	No data available	Not applicable
Boiling point / boiling range	No data available	Not applicable
Flash point	> 61 °C	Not applicable
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	< 1100	hPa @ 50 °C
Vapour density	No data available	
Relative density	No data available	None known
Water solubility	Slightly soluble	
Solubility(ies)	No data available	
Partition coefficient	No data available	

SAFETY DATA SHEET

BOSTIK GLASIL OFF WHITE
Supercedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	7500 - 10500 Pa.s	Spindle 4 @ 1 rpm @ 23 °C
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available
Softening Point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	ca. 1.5 g/cm ³
Bulk density	No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Classification is based on additional test data from raw material supplier.

SAFETY DATA SHEET

BOSTIK GLASIL OFF WHITE
Supercedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 3,940.20 mg/kg
ATEmix (inhalation-vapour) 1,472.85 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Silane, ethenyltrimethoxy- 2768-02-7	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3360 µL/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine 100545-48-0	LD50 >2000 mg/kg (Rattus)		LC50 =5.05 mg/kg (Rattus)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Component Information					
Silane, ethenyltrimethoxy- (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 431: In Vitro Skin Corrosion: Human Skin Model Test	EPISKIN™	in vitro	0.02 g	4 hours	Non-irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Component Information					
Silane, ethenyltrimethoxy- (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye	0.1 mL	72 hours	Non-irritant

Respiratory or skin sensitisation Repeated or prolonged contact may cause allergic reactions in very susceptible persons.

Component Information					
Silane, ethenyltrimethoxy- (2768-02-7)					

SAFETY DATA SHEET

BOSTIK GLASIL OFF WHITE
Supersedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Sensitizing > 25 %

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information		
Silane, ethenyltrimethoxy- (2768-02-7)		
Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

Component Information		
Silane, ethenyltrimethoxy- (2768-02-7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)		
Method	Species	Results
OECD Test No. 421: Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Component Information					
Silane, ethenyltrimethoxy- (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor

SAFETY DATA SHEET

BOSTIK GLASIL OFF WHITE
Supersedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

	plants		Micro-organisms			(long-term)
Silane, ethenyltrimethoxy-2768-02-7	EC 50 (72h) > 957 mg/l (Desmodosmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine 100545-48-0	EL50 (72h) >100 mg/L Algae (Pseudokirchneriella subcapitata)	LL50 (96h) >10mg/L (Onchohynchus mykiss)	-	EL50 (48h) >10mg/L Daphnia (Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information			
Silane, ethenyltrimethoxy- (2768-02-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Silane, ethenyltrimethoxy-2768-02-7	1.1	-

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment . This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).

Chemical name	PBT and vPvB assessment
Silane, ethenyltrimethoxy-2768-02-7	The substance is not PBT / vPvB
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine 100545-48-0	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international

SAFETY DATA SHEET

BOSTIK GLASIL OFF WHITE
Supercedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

	regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN Number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

IMDG

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine Pollutant	Np
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Diocetyl tin oxide	870-08-6	20

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

SAFETY DATA SHEET

BOSTIK GLASIL OFF WHITE
Supercedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

France

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) WGK 1

TRGS - 510 Storage Class Storage Class 10 : Combustible liquids

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H317 - May cause an allergic skin reaction

H332 - Harmful if inhaled

H412 - Harmful to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average)

Ceiling Maximum limit value

STEL
*

STEL (Short Term Exposure Limit)
Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure

STOT SE Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

Key literature references and sources for data

SAFETY DATA SHEET

BOSTIK GLASIL OFF WHITE
Supersedes Date: 18-Nov-2019

Revision date 18-Nov-2019
Revision Number 1

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 18-Nov-2019

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet