



# LIGHT HAND SCREED-LH

## TECHNICAL DATASHEET

Version: 2019-06-11

### PRODUCT DESCRIPTION

A medium-grade, easy-to-apply hand screed with good filling capability.

### AREA OF USAGE

Suitable for screeding of plaster joints and surfaces, concrete, lightweight concrete and panel materials in dry rooms indoors. The screed is also suitable for use on splice strips. A paper strip should be used when screeding plasterboard.

### WORKING INSTRUCTION

Surfaces should be clean, dry and firm. Applied by hand with a trowel. When screeding plasterboard, the splice strips are placed directly into the screed. Screeded surfaces should be sanded with sandpaper, grain size 100-120, then wiped down and primed before wallpapering or painting.

### SAFETY

The product's contents are not classified as hazardous to health or flammable pursuant to applicable legislation. The filler can cause eye irritation during grinding and sanding, which is why safety goggles should be used. For more information, please see the safety data sheet.

### CONTACT US

TEL +46 (0)42-19 50 00

info.se@bostik.com



## TECHNICAL DATA

| Properties           |                                                                                                                 |
|----------------------|-----------------------------------------------------------------------------------------------------------------|
| Colour               | Light grey                                                                                                      |
| Filler               | White dolomite marble and light filler                                                                          |
| Grain size           | 0 - 0.15 mm                                                                                                     |
| Binder               | Cellulose derivative, polymer dispersion                                                                        |
| Thinning             | Water. Should not normally be thinned.                                                                          |
| Cleaning             | Tools should be cleaned with water                                                                              |
| Density              | 1.1                                                                                                             |
| Drying time          | Approx. 8-10 hours depending on temperature, humidity and layer thickness. Completely dry after about 24 hours. |
| Layer thickness      | Max. 4 mm                                                                                                       |
| Material consumption | Approx. 0.3 litres/m <sup>2</sup> for screeding of joints two times on plasterboard                             |
| .                    | Approx. 1 litre/m <sup>2</sup> for screeding of surfaces with 1 mm layer thickness                              |
| Working temperature  | Can be applied from +5 to +30°C, optimal temperature 18-20°C                                                    |
| Storage              | Cool but frost-free                                                                                             |
| Storage time         | 1 year in unopened packaging at +20°C.                                                                          |
| Flammability         | Does not spread or maintain fire.                                                                               |

## CONTACT US

TEL +46 (0)42-19 50 00

info.se@bostik.com

