



# LIGHT SCREED COARSE LG

## TECHNICAL DATASHEET

Version: 2019-06-11

### PRODUCT DESCRIPTION

A coarse-grain hand screed with extra high filling capability and adhesion

### AREA OF USAGE

Suitable for screeding of mortar and plastered surfaces, brick walls etc. and for repairs of damage and holes indoors in dry areas. The very high filling capability means that this screed is particularly well suited to screeding of large surface areas on walls and ceilings.

### WORKING INSTRUCTION

Surfaces should be clean, dry and firm. Applied by hand with a trowel. If a finer surface is desired, perform after-screeding with a medium-grain or fine screed. Screeded surfaces should be sanded with sandpaper, grain size 100-120, then wiped down and primed before wallpapering or painting.

### SAFETY

The product's contents are not classified as hazardous to health or flammable pursuant to applicable legislation. The filler can cause eye irritation during grinding and sanding, which is why safety goggles should be used. For more information, please see the safety data sheet.

### CONTACT US

TEL +46 (0)42-19 50 00

[info.se@bostik.com](mailto:info.se@bostik.com)



## TECHNICAL DATA

Colour	Grey
Filler	White dolomite marble and light filler
Grain size	0 - 0.30 mm
Binder	Cellulose derivative, polymer dispersion
Thinning	Water. Should not normally be thinned.
Cleaning	Tools should be cleaned with water
Density	0.8
Drying time	Approx. 8-10 hours depending on temperature, humidity and layer thickness. Completely dry after about 24 hours.
Layer thickness	Max. 15 mm
Material consumption	Approx. 1 litre/m <sup>2</sup> for screeding of surfaces with 1 mm layer thickness
Working temperature	Can be applied from +5 to +30°C, optimal temperature 18-20°C
Storage	Cool but frost-free
Storage time	1 year in unopened packaging at +20°C.
Flammability	Does not spread or maintain fire

## CONTACT US

TEL +46 (0)42-19 50 00

info.se@bostik.com

