



# ULTRA FINO FINISHING PUTTY

READY-TO-USE ALL-PURPOSE PUTTY

DESCRIPTION

**ULTRAFINO FINISHING PUTTY** is an all-around, ready-to-use, high grade acrylic-based finishing putty suitable to a wide range of non-structural filling, levelling and patchwork of gypsum board, fiber cement board, plasterboard, wood and concrete as well as a finishing coat prior to painting. It provides smooth and seamless wall and ceiling surfaces ready to receive desired architectural finish or coating.

FEATURES AND BENEFITS

- Provides smooth finish
- Less sanding required
- Superior hiding power

RECOMMENDED USES

- Filling joints between gypsum boards, fiber cement boards, plasterboards, wood or plywood
- Leveling or patchwork over concrete, wood or similar substrates for interior and covered or weather protected outdoor areas.
- Embedding fasteners, reinforcing tape and other trims.
- Filling dents, knots and nail holes in woodwork
- Concrete finishing coat prior to painting

SUBSTRATE PREPARATION

The surface must be clean, sound and free from any dust, contaminants, loose particles and/or laitance, oil, paint, curing compound and other coatings.

METHOD OF APPLICATION

1. Stir the ULTRAFINO FINISHING PUTTY thoroughly to restore smooth and homogeneous consistency. The mixture is ready-to-use, do not add water to avoid cracking and excessive shrinkage.
2. Apply several light strokes to cover the application areas. The mixture can also be used as finishing coat, apply as necessary to completely cover areas.
3. Sand the final coat prior to finishing. Follow the paint manufacturer's instruction for paint application.



TEST PARAMETER	TECHNICAL DATA
Color	Off-White
Form	Paste
Texture	Smooth, Free from lumps
Viscosity, RT (#6,20rpm)	>500,000 cps
pH Value	8.0 - 9.0
Workability	Non-sticking & good drying
Sandability	Excellent
Adhesion to Gypsum Board & FCB	Excellent
Gap Filling Capability	20mm wide; 10mm deep
% Solids	>70%

**COVERAGE**

1 kg of ULTRAFINO Finishing Putty covers approximately 3 linear meters of taped joints at 15 cm width or 2-2.5 sqm2 as finishing coat.

**STORAGE/SHELF LIFE**

Store in a cool dry place not exceeding 30°C. In its original and unopened packaging, ULTRAFINO FINISHING PUTTY will remain usable for a period of 12 months from the date of manufacture.

**PACKAGING**

25 kg pail, 5 kg and 1 kg

**DISCLAIMER:**

The information in this Technical Data Sheet is intended for the assistance of users and is of a general nature. It reflects the extent of our knowledge and experience of our products and is based on tests which we believe to be reliable. However, no guarantee of accuracy can be given due to the wide range of surfaces, environmental and field conditions and variations encountered in raw materials, manufacturing equipment and methods at the place where the work is performed. Some of these will be beyond our knowledge and control. Users are asked to make sure that the TDS in their possession is the latest issue. Likewise, we recommend users carry out their own tests to determine the suitability of the product for their particular purposes.

Any claim for a defective product must be filed within 30 days of discovery of a problem and must be submitted with written proof of purchase. Claims are not transferrable or assignable and extend only to the original purchaser/user. Bostik reserves the right to inspect alleged failure and no responsibility will be accepted unless Bostik is given the opportunity to do so. Bostik limits its liability to the replacement of the product/s proven faulty.