

**BOSTIK PUREFIX SUPER POWER**  
Supersedes Date: 03-Mar-2020

Revision date 02-Mar-2020  
Revision Number 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product Identifier

**Product Name** BOSTIK PUREFIX SUPER POWER  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant.  
**Uses advised against** None known.

### 1.3. Details of the supplier of the safety data sheet

**Company Name**  
Bostik SA  
420 rue d'Estienne d'Orves  
92700 Colombes  
FRANCE  
Tel: +33 (0)1 49 00 90 00

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**Emergency Telephone** No information available

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

### 2.2. Label Elements

Not classified

**Signal word**  
Not classified

**Hazard statements**  
Not classified

### EU Specific Hazard Statements

EUH210 - Safety data sheet available on request.

EUH208 - Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine & 1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)propyl]- & Dioctyltinbis(acetylacetonate). May produce an allergic reaction.

### Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P280 - Wear protective gloves and eye/face protection.

# SAFETY DATA SHEET

**BOSTIK PUREFIX SUPER POWER**  
Supercedes Date: 03-Mar-2020

Revision date 02-Mar-2020  
Revision Number 1

## 2.3. Other Hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

## PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

The product contains no substances which at their given concentration, are considered to be hazardous to health

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Trimethoxyvinylsilane	220-449-8	2768-02-7	1 - <2.5	Acute Tox. 4 (H332) Flam. Liq. 3 (H226)		01-2119513215-52-XXXX
N-(3-(trimethoxysilyl)propyl)ethylenediamine	217-164-6	1760-24-3	0.1- <1	Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H332) STOT SE 3 (H335)		01-2119970215-39-XXXX
Diocetyl tinbis(acetylacetonate)	483-270-6	54068-28-9	0.1- <1	STOT SE 2 (H371) Skin Sens. 1 (H317)	Skin Sens. 1 :: C>=5%	01-0000020199-67-XXXX
1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)propyl]-	221-336-6	3069-29-2	0.1- <1	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317)		01-2119963926-21-xxxx

### Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

# SAFETY DATA SHEET

BOSTIK PUREFIX SUPER POWER  
Supersedes Date: 03-Mar-2020

Revision date 02-Mar-2020  
Revision Number 1

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Call a doctor immediately. If swallowed, rinse mouth with water (only if the person is conscious). Small amounts of toxic methanol are released by hydrolysis.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	None known.
-----------------	-------------

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Treat symptomatically.
------------------------	-------------------------------------------------------------------------------------------------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Water spray, carbon dioxide (CO <sub>2</sub> ), dry chemical, alcohol-resistant foam.
-------------------------------------	---------------------------------------------------------------------------------------

<b>Unsuitable extinguishing media</b>	Full water jet.
---------------------------------------	-----------------

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards arising from the chemical</b>	Thermal decomposition can lead to release of irritating gases and vapours.
---------------------------------------------------	----------------------------------------------------------------------------

<b>Hazardous combustion products</b>	Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ).
--------------------------------------	-----------------------------------------------------

### 5.3. Advice for firefighters

<b>Special protective equipment for fire-fighters</b>	Wear self contained breathing apparatus for fire fighting if necessary.
-------------------------------------------------------	-------------------------------------------------------------------------

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.
-----------------------------	--------------------------------------------------------------------------------------------------------------------------

<b>Other information</b>	Ventilate the area. Prevent further leakage or spillage if safe to do so.
--------------------------	---------------------------------------------------------------------------

<b>For emergency responders</b>	Use personal protection recommended in Section 8.
---------------------------------	---------------------------------------------------

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.
----------------------------------	--------------------------------------------------------------------------------------------------------------------------------------

# SAFETY DATA SHEET

BOSTIK PUREFIX SUPER POWER  
Supercedes Date: 03-Mar-2020

Revision date 02-Mar-2020  
Revision Number 1

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep at temperatures between 5 and 35 °C. Protect from sunlight. Keep away from food, drink and animal feedingstuffs.

### 7.3. Specific end use(s)

**Specific Use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

**Exposure Limits** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

**Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.**

Chemical name	European Union
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> *

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)	
Trimethoxyvinylsilane (2768-02-7)	
Type	worker Systemic health effects Long term
Exposure route	Inhalation
Derived No Effect Level (DNEL)	27,6 mg/m <sup>3</sup>

Type	worker Systemic health effects Long term
Exposure route	Dermal

# SAFETY DATA SHEET

**BOSTIK PUREFIX SUPER POWER**  
**Supersedes Date:** 03-Mar-2020

**Revision date** 02-Mar-2020  
**Revision Number** 1

Derived No Effect Level (DNEL)	3,9 mg/kg bw/d
--------------------------------	----------------

### **N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)**

Type	worker Systemic health effects Long term
Exposure route	Inhalation
Derived No Effect Level (DNEL)	35.5 mg/m <sup>3</sup>

Type	worker Systemic health effects Long term
Exposure route	Dermal
Derived No Effect Level (DNEL)	5 mg/kg bw/d

### **Diocetylbinbis(acetylacetonate) (54068-28-9)**

Type	Long term Systemic health effects worker
Exposure route	Dermal
Derived No Effect Level (DNEL)	0.07 mg/kg bw/d

Type	Long term Systemic health effects worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	84 mg/m <sup>3</sup>

Type	Short term Systemic health effects worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	84 mg/m <sup>3</sup>

Type	Long term Short term Local health effects worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.091 mg/m <sup>3</sup>

### **1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)propyl]- (3069-29-2)**

Type	worker Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	12 mg/m <sup>3</sup>

Type	worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	1.7 mg/kg bw/d

### **Derived No Effect Level (DNEL)**

#### **Trimethoxyvinylsilane (2768-02-7)**

Type	Consumer Systemic health effects Long term
Exposure route	Inhalation
Derived No Effect Level (DNEL)	18,9 mg/m <sup>3</sup>

Type	Consumer Systemic health effects Long term
Exposure route	Dermal
Derived No Effect Level (DNEL)	7,8 mg/kg bw/d

Type	Consumer Systemic health effects Long term
Exposure route	Oral
Derived No Effect Level (DNEL)	0,3 mg/kg bw/d

### **N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)**

Type	Consumer Systemic health effects Long term
Exposure route	Oral
Derived No Effect Level (DNEL)	2.5 mg/kg bw/d

Type	Consumer Systemic health effects Long term
Exposure route	Inhalation

# SAFETY DATA SHEET

**BOSTIK PUREFIX SUPER POWER**  
**Supersedes Date:** 03-Mar-2020

**Revision date** 02-Mar-2020  
**Revision Number** 1

Derived No Effect Level (DNEL)	8.7 mg/m <sup>3</sup>
--------------------------------	-----------------------

Type	Consumer Systemic health effects Long term
Exposure route	Dermal
Derived No Effect Level (DNEL)	2.5 mg/kg bw/d

## 1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)propyl]- (3069-29-2)

Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	2.9 mg/m <sup>3</sup>

Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	0.83 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	0.83 mg/kg bw/d

**Predicted No Effect Concentration (PNEC)** No information available.

## Predicted No Effect Concentration (PNEC)

### Trimethoxyvinylsilane (2768-02-7)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

### N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.0062 mg/l
Sewage treatment plant	25 mg/l

### Diocetyl tinbis(acetylacetonate) (54068-28-9)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	26 µg/l
Marine water	2.6 µg/l
Freshwater - intermittent	260 µg/l
Sewage treatment plant	1 mg/l
Freshwater sediment	0.155 mg/kg dry weight
Marine sediment	0.0155 mg/kg dry weight
Soil	0.0158 mg/kg dry weight

### 1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)propyl]- (3069-29-2)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.006 mg/l
Sewage treatment plant	25 mg/l
Freshwater sediment	0.24 mg/kg dry weight
Marine sediment	0.024 mg/kg dry weight
Soil	0.01 mg/kg dry weight

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal Protective Equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166

# SAFETY DATA SHEET

BOSTIK PUREFIX SUPER POWER  
Supersedes Date: 03-Mar-2020

Revision date 02-Mar-2020  
Revision Number 1

<b>Hand protection</b>	Wear suitable gloves. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Glove thickness > 0.7mm. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Gloves must conform to standard EN 374
<b>Skin and body protection</b>	None under normal use conditions.
<b>Respiratory protection</b>	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
<b>Recommended filter type:</b>	Brown. Organic gases and vapours filter conforming to EN 14387. White.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	Paste
<b>Colour</b>	White
<b>Odour</b>	Characteristic
<b>Odour threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	> 100 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	No data available	
Water solubility	Immiscible in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

### 9.2. Other information

<b>Solid content (%)</b>	No information available	
<b>VOC Content (%)</b>	>= 34.3 g/L / 2.23 %	European directive n°2010/75/UE
<b>Density</b>	1.54 g/cm <sup>3</sup>	

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Product cures with moisture.

### 10.2. Chemical stability

# SAFETY DATA SHEET

BOSTIK PUREFIX SUPER POWER  
Supersedes Date: 03-Mar-2020

Revision date 02-Mar-2020  
Revision Number 1

**Stability** Stable under normal conditions.

## Explosion Data

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

## 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

## 10.4. Conditions to avoid

**Conditions to avoid** Protect from moisture.

## 10.5. Incompatible materials

**Incompatible materials** None known based on information supplied.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

##### Product Information

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact** Based on available data, the classification criteria are not met.

**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

#### Numerical measures of toxicity

##### Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (dermal)** 3,571.90 mg/kg

**ATEmix (inhalation-vapour)** 716.50 mg/l

##### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane 2768-02-7	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3360 µL/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44 mg/L air



# SAFETY DATA SHEET

**BOSTIK PUREFIX SUPER POWER**  
**Supersedes Date:** 03-Mar-2020

**Revision date** 02-Mar-2020  
**Revision Number** 1

Diocetylbinbis(acetylacetonate) 54068-28-9	LD50 =2500 mg/kg (Rattus)	LD50 >2000 mg/kg (Rattus)	
1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)pro pyl]- 3069-29-2	=200 - 2000 mg/Kg (Rattus) (OECD 401)	>5000 mg/Kg (Oryctolagus cuniculus) (OECD 402)	

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

### **Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit				Mild skin irritant

1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)propyl]- (3069-29-2)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			irritant

### **Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)propyl]- (3069-29-2)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit				Eye Damage

### **Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal Injection	Not a skin sensitiser

Component Information			
Trimethoxyvinylsilane (2768-02-7)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	sensitising

# SAFETY DATA SHEET

**BOSTIK PUREFIX SUPER POWER**  
**Supersedes Date:** 03-Mar-2020

**Revision date** 02-Mar-2020  
**Revision Number** 1

1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)propyl]- (3069-29-2)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig		Sensitizing

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

**Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio)	-	EC50 (48h) =81mg/L Daphnia magna		

# SAFETY DATA SHEET

**BOSTIK PUREFIX SUPER POWER**  
Supersedes Date: 03-Mar-2020

Revision date 02-Mar-2020  
Revision Number 1

		erio)Semi-static		Static		
Diocetylbinbis(acetylacet onate) 54068-28-9	-	LC50 (96h) =86 mg/L (Static)	-	EC50 (48h) =58.6 mg/L (Daphnia magna)		

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Component Information			
Trimethoxyvinylsilane (2768-02-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

## 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

### Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Trimethoxyvinylsilane 2768-02-7	1.1	-
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-0.3	-

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The components in this formulation do not meet the criteria for classification as PBT or vPvB. .

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane 2768-02-7	The substance is not PBT / vPvB
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	The substance is not PBT / vPvB
Diocetylbinbis(acetylacetate) 54068-28-9	The substance is not PBT / vPvB
1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)propyl]- 3069-29-2	The substance is not PBT / vPvB

## 12.6. Other adverse effects

**Other adverse effects** No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international

# SAFETY DATA SHEET

BOSTIK PUREFIX SUPER POWER  
Supercedes Date: 03-Mar-2020

Revision date 02-Mar-2020  
Revision Number 1

---

	regulations as applicable.
<b>Contaminated packaging</b>	Handle contaminated packages in the same way as the product itself.
<b>Waste codes / waste designations according to EWC / AVV</b>	Waste codes should be assigned by the user based on the application for which the product was used.
<b>European Waste Catalogue</b>	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN Number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

### IMDG

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine Pollutant	Np
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

# SAFETY DATA SHEET

**BOSTIK PUREFIX SUPER POWER**  
Supercedes Date: 03-Mar-2020

Revision date 02-Mar-2020  
Revision Number 1

## **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

## **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

## **Persistent Organic Pollutants**

Not applicable

## **National Regulations**

### **France**

### **Germany**

#### **Ordinance on Industrial Safety and Health - Germany - BetrSichV**

No flammable liquids in accordance with BetrSichV

**Water hazard class (WGK)**                      WGK 1

### **Netherlands**

#### **List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)**

**MAL-Code** 1-1 (1993)

### **Sweden**

Occupational exposure limits AFS 2018:1

## **15.2. Chemical safety assessment**

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### **Key or legend to abbreviations and acronyms used in the safety data sheet**

#### **Full text of H-Statements referred to under section 3**

H226 - Flammable liquid and vapour  
H302 - Harmful if swallowed  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation

# SAFETY DATA SHEET

**BOSTIK PUREFIX SUPER POWER**  
**Supersedes Date:** 03-Mar-2020

**Revision date** 02-Mar-2020  
**Revision Number** 1

---

H371 - May cause damage to organs

## Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 02-Mar-2020

## Indication of changes

**Revision note** Not applicable.

**Training Advice** When working with hazardous materials, regular training of operators is required by law

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**