

# A315

## NO-MORE NAILS PREMIUM POWERFUL INSTANT GRAB ACRYLIC DECORATORS ADHESIVE

### TECHNICAL DATA SHEET

#### BENEFITS

- Solvent free
- Suitable for EPS and XPS
- Almost odourless
- Easy to apply and clean
- Non corrosive towards metal

#### PRODUCT DESCRIPTION

**Bostik A315 NO MORE NAILS PREMIUM** is a versatile adhesive based on acrylic dispersion. The adhesive cures due to evaporation of water to form a strong and durable bond.

#### APPLICATIONS

**Bostik A315 NO MORE NAILS PREMIUM** was specifically developed for bonding wood, chipboard, hardboard and uPVC to brick work, stone or concrete. Also suitable for EPS and XPS and bonding ceramic tiles to porous substrates. For interior use.

#### DIRECTIONS OF USE

Apply as an adhesive in a 'ventilating' way in vertical stripes or dots with 20 – 40 cm distance in between stripes. The material must be put into place by shoving and pushing firmly. For further questions, please consult our technical department.



#### TECHNICAL DATA

Application temperature		+5°C to + 40°C
Base		Acrylic dispersion
Curing time	@ +23°C/50% RH	3 days
Density	ISO 1183-1	1,90 g/ml
Flow	ISO 7390	< 2 mm
Frost resistance during transportation		Up to - 15°C
Open Time	@ +23°C/50% RH	5-10 min.
Temperature resistance		-20°C to + 75°C
Usage		600 ml/m <sup>2</sup>

*These values are typical properties and may vary +/-3%*

#### LIMITATIONS

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Not suitable for continuous exposure to water
- Not suitable for movement joints

#### SURFACE PREPARATIONS AND FINISHING

Application temperature + 5°C to + 40°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Substrates to be cleared of all loose particles, absorbent substrates do not need to be absolutely dry. Very porous substrates like: gypsum, aerated concrete, limestone, etc, need to be primed with a mixture of 1 part **Bostik A315 NO MORE NAILS PREMIUM** and 2 parts water. Always test adhesion prior to application. Finish and smooth with water.

#### CLEANING

Uncured material and tools can be cleaned by using **Bostik T100 UNIVERSAL CLEANER**. Cured material can only be mechanically removed. Hands can be cleaned with **Bostik T150 CLEANING WIPES**.

## COLOUR(S)

- White

## PACKAGING

- 300 ml Cartridge, 12 per box

*For product specifications, please refer to the Online Product Detail Page*

## SHELF LIFE

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 18 months from production date, stored in a dry place.

## HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and at [www.bostik.com](http://www.bostik.com).

## CERTIFICATIONS

- A+ French VOC Regulation

The information and recommendations relating to the application and end-use of the product are given in good faith and based on tests which we believe to be reliable. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. However, no warranty in respect of merchantability or fitness for a particular purpose, nor any liability arising out of any legal relationship, whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. No guarantee of their accuracy can be made because of the great range of field conditions and variation encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with limited warranty only, and on condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik be liable to anyone except for replacement of the products or refund of the purchase price.

## Bostik

De Voerman 8 • NL-5215 MH 's-Hertogenbosch  
Tel.: +31 (0) 73 6244 244  
[www.bostik.com](http://www.bostik.com)

## BOSTIK SMART SUPPORT

Smart help digital  
[Bostik.com](http://Bostik.com)

Smart help  
+31 (0)162 491 000

