



DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Product name:

BOSTIK 2730 MS

DoP-Nr. **15651-1-14-45**

1. Product classification code:

EN 15651-1:2012: F Ext-Int CC 12,5E

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch-No.: see product packaging/labeling

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Joint sealant for indoor and outdoor facades,
Cold Climate (CC) included**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Bostik GmbH, An der Bundesstraße 16, DE-33829 Borgholzhausen

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 plus 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

A notified testing laboratory, the MPA-Braunschweig, NB 0761, has performed the determination of the product-type on the basis of Initial Type Testing (ITT) under system 3 and issued a corresponding test report.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant

9. Declared performance

Conditioning: procedure B

Substrates: mortar M1 and glass with primer

Essential Product Features	Performance	Harmonized Technical Specification
Reaction to fire (EN 13501-1)	Class E	EN 15651-1:2012
Release of dangerous substances	NPD	
Resistance to flow (EN ISO 7390)	≤ 3 mm	
Loss of volume (EN ISO 10563)	≤ 25 %	
Tensile properties at maintained extension (EN ISO 8340)	Passed (NF)	
Adhesion/cohesion at variable temperatures (EN ISO 9047)	Passed (NF)	
Adhesion/cohesion at maintained extension and after immersion in water (EN ISO 10590)	Passed (NF)	
Elastic recovery (EN ISO 7389)	≥ 40 %	
Tensile properties at maintained extension at - 30 °C (EN ISO 8340)	Passed (NF)	
Durability	Passed	

10. The performance of the product identified in section 1 and 2 is in conformity with the performance declared in section 9. This declaration of performance is issued under the sole responsibility of the manufacturer as identified in section 4.

Signed for and on behalf of Bostik GmbH by Company Management



Borgholzhausen, 01.07.2014

Managing Director (MD)

Bostik GmbH

An der Bundesstraße 16, 33829 Borgholzhausen, Germany, Postfach 1154, 33825 Borgholzhausen, Germany

Phone: + 49 (0) 5425 801-0, Fax: + 49 (0) 5425 801-140, E-mail: info.germany@bostik.com

Amtsgericht Gütersloh HRB 4939, Geschäftsführer: Roland Albers, Olaf Memmen

Hypo Vereinsbank, BIC HYVEDEMM488, IBAN DE97 1002 0890 0355 2397 64

A company of TOTAL

www.bostik.de