



DECLARATION OF PERFORMANCE  
in accordance with Annex III of Regulation (EU) No 305/2011  
(Construction Product Regulation)

**DoP \_ [EN] \_ 001\_No 57001066-1501**

1. Unique identification code of product-type:  
**Bostik P795 SEAL'N'FLEX PREMIUM**
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):  
**Batch number: See product packaging**
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:  
**Sealants for façade elements  
Sealants for pedestrian walkways  
EN 15651-1: F-EXT-INT-CC (CLASS 25HM)  
EN 15651-4: PW-EXT-INT-CC (CLASS 25HM)**
4. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):  
**BOSTIK BENELUX B.V. ■ DENARIUSSTRAAT 11 ■ NL - 4903 RC OOSTERHOUT**
5. Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2): not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 3  
System 3 for reaction to fire**
7. In case of declaration of performance concerning a construction product covered by a harmonized standard:  
**The notified body SKZ – TeConA GmbH (1213) performed the initial type testing according to EN 15651-1 / EN 15651-4 and reaction to fire under system 3 and issued a: test report.**

**Bostik Benelux B.V.**  
Denariusstraat 11, NL-4903 RC Oosterhout, The Netherlands  
Phone: +31 (0)162 491 000, E-mail: info@denbraven.nl  
[www.denbraven.com](http://www.denbraven.com)



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not relevant
9. Declared performance:  
 Conditioning: Procedure A (according to ISO 8340)  
 Substrate: Mortar M2 (without primer)  
 Anodised aluminium (without primer)

| Essential characteristics  | Performance    | Harmonized technical specification |
|--|----------------|------------------------------------|
| Reaction to fire   | <b>Class E</b> | <b>EN 15651-1:2012</b>             |
| Release of chemicals dangerous to the environment and health                     | <b>NPD (*)</b> |                                    |
| <b>Water tightness and air tightness</b>   |                |                                    |
| Resistance to flow   | <b>≤ 3 mm</b>  |                                    |
| Loss of volume   | <b>≤ 10 %</b>  |                                    |
| Tensile properties at maintained extension after water immersion                 | <b>NF</b>      |                                    |
| Tensile properties (secant modulus) for use in cold climate areas (-30°C)        | <b>Nr</b>      |                                    |
| Tensile properties at maintained extension for use in cold climate areas (-30°C) | <b>NF</b>      |                                    |
| <b>Durability</b>  | <b>Pass</b>    |                                    |

**Bostik Benelux B.V.**  
 Denariusstraat 11, NL-4903 RC Oosterhout, The Netherlands  
 Phone: +31 (0)162 491 000, E-mail: info@denbraven.nl  
[www.denbraven.com](http://www.denbraven.com)



Conditioning: Procedure B (according to ISO 8340)  
 Substrate: Mortar M2 (with primer P250)

| Essential characteristics   | Performance                                  | Harmonized technical specification |
|---|--|------------------------------------|
| Reaction to fire  | <b>Class E</b>                               | <b>EN 15654-1:2012</b>             |
| Release of chemicals dangerous to the environment and health                              | <b>NPD (*)</b>                               |                                    |
| <b>Water tightness and air tightness</b>  |  |                                    |
| Tensile properties at maintained extension  | <b>NF</b>                                    |                                    |
| Loss of volume  | <b>≤ 10 %</b>                                |                                    |
| Tear resistance   | <b>NF</b>                                    |                                    |
| Adhesion / cohesion properties at maintained extension after 28 days water immersion      | <b>NF / change of secant modulus: ≤ 50 %</b> |                                    |
| Adhesion / cohesion properties at maintained extension after 28 days salt water immersion | <b>NF</b>                                    |                                    |
| Tensile properties (secant modulus) for use in cold climate areas (-30°C)                 | <b>NR</b>                                    |                                    |
| Tensile properties at maintained extension for use in cold climate areas (-30°C)          | <b>NF</b>                                    |                                    |
| <b>Durability</b>   | <b>Pass</b>                                  |                                    |

(\*) See material safety data sheet  
 NPD: No Performance Determined  
 NF: No Failure  
 NR: Not Required

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not relevant  
 Substrate: Mortar M1 (with primer P03)

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Bostik Benelux B.V.**  
 Denariusstraat 11, NL-4903 RC Oosterhout, The Netherlands  
 Phone: +31 (0)162 491 000, E-mail: info@denbraven.nl  
[www.denbraven.com](http://www.denbraven.com)



Signed for and on behalf of the manufacturer by:

A handwritten signature in blue ink, appearing to read "V. Imbos", written over a horizontal line.

Vincent Imbos *V. Imbos*  
Managing Director  
Oosterhout, 12/2018

**Bostik Benelux B.V.**  
Denariusstraat 11, NL-4903 RC Oosterhout, The Netherlands  
Phone: +31 (0)162 491 000, E-mail: [info@denbraven.nl](mailto:info@denbraven.nl)  
[www.denbraven.com](http://www.denbraven.com)