



J125 Flexible Grout

MOULD RESISTANT WALL & FLOOR TILE GROUT

Date: 25 November 2019

Fact Sheet No.: TDS01627

YOUR SMART ADVANTAGES

- Suitable for swimming pools and power showers
- Mould and efflorescence resistant
- Fills deep joints in one application

USES

Bostik J125 Flexible Grout is a professional quality, cementitious polymer modified grout for walls and floors. It is formulated for narrow and wide joints and is easy to clean off, non-slump and dries with a very hard finish.

Bostik J125 Flexible Grout is suitable for use with all types of ceramic and porcelain tiles, mosaics, natural stone, marble, and quarry tiles. It is suitable for joints between 2mm to 15mm for both interior and exterior use.

PRODUCT CHARACTERISTICS

Colours	Grey, White, Jasmine, Limestone, Sandstone, and Anthracite																		
Form	Cementitious powder																		
Specific Gravity	Approx. 1.8																		
Composition	Polymer modified cement based formulation																		
Product Codes	<table border="0"> <tr> <td>30811628</td> <td>Grey</td> <td>5kg</td> </tr> <tr> <td>30811645</td> <td>Grey</td> <td>10kg</td> </tr> <tr> <td>30811624</td> <td>White</td> <td>5kg</td> </tr> <tr> <td>30811647</td> <td>White</td> <td>10kg</td> </tr> <tr> <td>30811629</td> <td>Jasmine</td> <td>5kg</td> </tr> <tr> <td>30811646</td> <td>Jasmine</td> <td>10kg</td> </tr> </table>	30811628	Grey	5kg	30811645	Grey	10kg	30811624	White	5kg	30811647	White	10kg	30811629	Jasmine	5kg	30811646	Jasmine	10kg
30811628	Grey	5kg																	
30811645	Grey	10kg																	
30811624	White	5kg																	
30811647	White	10kg																	
30811629	Jasmine	5kg																	
30811646	Jasmine	10kg																	

	30811630 Limestone 5kg
	30811631 Sandstone 5kg
	30811632 Anthracite 5kg
Storage/Shelf Life	Store and transport this bag securely in an upright position. Store for up to 12 months from date of manufacture when stored clear of the ground under cool, dry conditions within the temperature range of 5°C to 30°C. Protect from frost.

TYPICAL PERFORMANCE DATA (approx.)

Application Temperature	5°C to 25°C
Mix Ratio	Approx. 1.1 litres of water to 5kg of Bostik J125 Flexible Grout
Coverage	Coverage is dependent upon tile and joint dimensions. See coverage section below for more detailed calculation methods.
Open Time	Approx. 2 hours at 20°C
Drying Times	Walk on: 12 hours at 20°C Full cure: 72 hours at 20°C

DIRECTIONS FOR USE

IMPORTANT: IMPORTANT: Before using Bostik J125 Flexible Grout refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

Tiling and grouting should be carried out in accordance with the relevant British Standards Codes of Practice.

PREPARATION

1. Ensure that tiles are firmly fixed and adhesive is completely set. Bostik standard set adhesives should normally be left for at least 24 hours before grouting. Bostik rapid setting adhesives should be left for at least 2 to 3 hours, however these times will be increased by sealed or impervious substrates or at low ambient temperatures or high humidity.
2. Ensure tile and joints are clean, dry and free from dust grease or any other contamination. Some tiles have a soft glaze which may be scratched during grouting and tiles with a matt or porous texture may be prone to staining. You are advised to test the grout on a spare tile for suitability before proceeding.
3. Variations in raw materials, application techniques, type of tile, substrate and environmental conditions can limit colour consistency. For these reasons as with all other manufacturer's we cannot guarantee a consistent colour every time. It is advised to test the grout on a spare tile for suitability before proceeding.

MIXING

4. Mix Bostik J125 Flexible Grout with clean, cold water in a clean container whilst mechanically stirring and mixing thoroughly to give a smooth, consistent and easily worked mortar.
5. The recommended mix proportions are approximately 1.1 litres of water to 5kg of Bostik J125 Flexible Grout.
6. Do not add more water than is necessary to achieve a smooth paste consistency and do not mix more than can be applied within 2 hour period.
7. It is favourable to let the mixture to stand for 1 minute before use.
8. No water should be added after the original mixing.
9. Any of the mix not used within 2 hours should be discarded.
10. When grouting over a large area which requires the use of multiple bags of grout, ensure that all bags are from the same batch and that a consistent and identical water addition ratio is used for each mix.

COVERAGE

Coverage is dependent upon tile size and joint dimensions. It can be calculated using the formula below:

$$\frac{(A+B) \times C \times D \times G}{A \times B} = \text{Kg/m}^2$$

A = Tile length B = Tile width C = Joint width
D = Joint depth G = Specific Gravity

Joint Width	Tile Size (mm)	Floor Grout required (kg)
5mm	200 x 200 x 6	0.5kg/m ²
8mm	300 x 300 x 10	1.0kg/m ²
10mm	200 x 100 x 8	2.0kg/m ²

APPLICATION

11. The grout should be worked deeply into the joints using a sponge, squeegee or rubber filling knife. Work diagonally from lower parts upwards.
12. Remove excess grout immediately by the use of a squeegee, working diagonally across the tiles taking care not to drag grout out of the joints.
13. After initial hardening (approx. 30 minutes) clean the tile surface with a damp sponge. Do not leave film on the surfaces of tiles as this will be very difficult to remove when hardened.
14. When the grout is dry, polish the tiles with a clean dry cloth.

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +44 (0) 1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik J125 Flexible Grout, available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com