



# Thermogrip® H1955

## HOT MELT ADHESIVE

### KEY FEATURES

- Low heat seal activation temperature
- Excellent blocking resistance
- Good thermal stability

### DESCRIPTION

H1955 is a hot melt lidding adhesive suitable for coating extrusion process applications. H1955 has a low heat seal activation temperature, and excellent adhesion to various films, including polypropylene, polyethylene and polyethylene terephthalate.

### PACKAGING

For packaging options please call your Bostik sales or technical representative.

### SHELF LIFE

Can be stored 730 days in a clean dry place, in its original package at an average temperature of 25°C or below. Storage temperature should not exceed 40°C.

### STORAGE & HANDLING

Wear safety gloves and goggles when handling molten adhesive to minimize the risk of burns.

### COUNTRY OF MANUFACTURE

United States

### CLEANUP PROCEDURE

Mineral oil or paraffin wax are recommended for cleanup but should not be used at temperatures that exceed the flash point as stated on the SDS. This procedure should be followed by a thorough purge with the adhesive.



### TYPICAL PHYSICAL PROPERTIES

Description	Results
Thermosel Viscosity (Brookfield - ASTM D3236)	68,200 cP @ 300°F 44,300 cP @ 325°F 29,250 cP @ 350°F 20,200 cP @ 375°F
Softening Point (Ring and Ball Herzog - ASTM E28)	197°F
Suggested Running Temperature	300 - 350°F
Density	0.95 g/cc @ 77°F


### FOOD LEGISLATION

It is the responsibility of our customers to determine that their use of Bostik product(s) is safe, lawful, and suitable for the intended application. Because of possible changes in laws and regulations, we cannot guarantee that the status of this product will remain unchanged. We recommend that customers continuing to use this product verify its status annually.

### HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet should be consulted for proper handling, clean up and spill containment before use. Keep containers covered to minimize contamination.

### VISCOSITY CURVE



### LIMITED WARRANTY

The Limited Warranty for this product can be found at [www.bostik-us.com/resource-center/warranties](http://www.bostik-us.com/resource-center/warranties) or by calling 1-800-726-7845 (choose option 2, then option 2 again). To the maximum extent allowed by law, Bostik disclaims all other express or implied warranties, including without limitation warranties of merchantability and fitness for a particular purpose. Unless otherwise stated in the limited warranty, the sole remedy for breach of warranty is replacement of the product or refund of the buyer's purchase price. Bostik disclaims any liability for direct, incidental, consequential, or special damages to the maximum extent allowed by law. Disclaimers of implied warranties may not be applicable to certain classes of buyers and some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. The Limited Warranty extends only to the original purchaser and is not transferable or assignable. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase.

### BOSTIK HOTLINE

Smart help  
**1-800-726-7845**

**Bostik, Inc.**  
11320 W. Watertown Plank Road  
Wauwatosa, WI 53226  
[www.bostik-us.com](http://www.bostik-us.com)



This document supersedes all previously published literature.  
10.31.2016