

POLYURETHANE & ACRYLIC SEALANTS

COLOUR SELECTION



IDEAL FOR • Pre-cast and tilt-up joint sealing • Fire-rated penetrations and wall/floor joints • Flooring and pavements

SEAL N FLEX 1

A low modulus flex, one component, Class A polyurethane sealant

When cured it will form a tough, flexible seal capable of cyclic expansion and contraction movement of 100% ($\pm 50\%$) of the original joint width.

Special Features

- Excellent durability - unaffected by normal weathering conditions
- Acoustic rating
- Paintable
- Australian made

COLOUR CHART



SEAL N FLEX FC


A high performance fast cure one component polyurethane sealant

When cured it will form a tough, flexible seal and bond capable of cyclic, expansion and contraction movement of 50% ($\pm 25\%$).

Special Features

- Excellent durability - unaffected by normal weathering conditions
- Fast tack free time and cure rate
- Paintable
- Australian made

COLOUR CHART



FIRECAULK


Fire rated acrylic sealant

When cured it will form a tough flexible fire rated seal capable of cyclic expansion and contraction movement of 25% ($\pm 12.5\%$) of the original installed width.

Special Features

- Fire rated up to 4hrs (AS1530.4)
- Acoustic rated to 67Rw
- CSIRO certified
- Australian made

COLOUR CHART



FIREBAN ONE

A Low modulus flex one component fire rated polyurethane joint sealant

When cured it will form a tough flexible fire rated seal capable of cyclic expansion and contraction movement of 50% ($\pm 25\%$) of the original installed width

Special Features

- Fire rated up to 4hrs (AS1530.4)
- Acoustic rated to 67Rw
- CSIRO certified
- Australian made

COLOUR CHART



NOTE: The colours on the palette are as close as possible to the actual colours as printing will allow. Actual colours may vary from batch to batch and therefore may differ.

COPYRIGHT 2018 BOSTIK AUSTRALIA THESE MATERIALS CANNOT BE COPIED OR REPRODUCED WITHOUT CONSENT. ALL RIGHTS RESERVED.