

DAMPFIX PU  
 Revision Number 3

Revision date 01-Aug-2019  
 Supersedes Date: 28-May-2018

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product Identifier

**Product Name** DAMPFIX PU  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Primers, Sealers, and Undercoaters.  
**Uses advised against** No information available.

### 1.3. Details of the supplier of the safety data sheet

**Company Name**  
 Bostik New Zealand Limited  
 19 Eastern Hutt Road Wingate,  
 Lower Hutt, New Zealand  
 Tel: 04-567 5119  
 Fax: 04-567 5412

**Manufacturer**  
 Bostik Australia Pty Ltd  
 51-71 High Street,  
 Thomastown Victoria  
 Australia  
 Tel: 613 9279-9333  
 Fax: 613 9279-9342

**ABN:** 79 003 893 838

### 1.4. Emergency telephone number

**Emergency Telephone** 24 Hr: 0800 243 622  
 +64 4 917 9888  
 Poison Centre : 0800 764 766

**E-mail address** SDS.AP@Bostik.com

## Section 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

Aspiration hazard	Category 1 (6.1E <sup>9</sup> )
Acute toxicity - Inhalation (Vapors)	Category 3 (6.1C)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 (6.1D)
Skin corrosion/irritation	Category 3 (6.3B)
Respiratory sensitization	Category 1 (6.5A)
Skin sensitization	Category 1 (6.5B)
Carcinogenicity	Category 2 (6.7B)
Reproductive toxicity	Category 1B (6.8A)
Hazardous to the Aquatic Environment - Acute Hazard	Category 3 (9.1D)
Flammable liquids	Category 4 (3.1D)

### 2.2. Label Elements



**Signal word**

Danger

# SAFETY DATA SHEET

**DAMPFIX PU**  
**Revision Number 3**

**Revision date** 01-Aug-2019  
**Supersedes Date:** 28-May-2018

---

## **Hazard statements**

H316 - Causes mild skin irritation  
H331 - Toxic if inhaled  
H360 - May damage fertility or the unborn child  
H351 - Suspected of causing cancer  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H304 - May be fatal if swallowed and enters airways  
H402 - Harmful to aquatic life  
H317 - May cause an allergic skin reaction  
H227 - Combustible liquid

## **Prevention**

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P281 - Use personal protective equipment as required  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray  
P271 - Use only outdoors or in a well-ventilated area  
P284 - In case of inadequate ventilation wear respiratory protection  
P272 - Contaminated work clothing should not be allowed out of the workplace  
P280 - Wear protective gloves  
P273 - Avoid release to the environment  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P235 - Keep cool

## **Inhalation**

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P311 - Call a POISON CENTER or doctor/physician

## **Skin**

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water  
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention  
P363 - Wash contaminated clothing before reuse

## **Ingestion**

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor  
P331 - Do NOT induce vomiting

## **Fire**

P370 + P378 - In case of fire: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam to extinguish

## **Storage**

P405 - Store locked up  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

## **Disposal**

P501 - Dispose of contents/ container to an approved waste disposal plant

## **2.3. Other Hazards**

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

# SAFETY DATA SHEET

DAMPFIX PU  
Revision Number 3

Revision date 01-Aug-2019  
Supersedes Date: 28-May-2018

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Mixture

### 3.2 Mixtures

Chemical name	CAS No.	Weight-%
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene	64742-48-9	10 - <20
Petroleum distillates, hydrotreated light	64742-47-8	1 - <5
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - <5
Urea,	77703-56-1	1 - <3
N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-Benzene, 1,3-diisocyanatomethyl-	26471-62-5	1 - <3
Ethylbenzene	100-41-4	1 - <3
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1- <1
Glycidoxypropyltrimethoxysilane	2530-83-8	0.1- <1
1-Methyl-2-pyrrolidone	872-50-4	0.1- <1
Dibutyltin dilaurate	77-58-7	0.1- <1

\*\*\* Any remaining ingredients are not hazardous

## Section 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General advice</b>	Immediate medical attention is required. If symptoms persist, call a physician.
<b>Inhalation</b>	Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Immediate medical attention is required. If not breathing, give artificial respiration. Oxygen or artificial respiration if needed. Call a physician. Immediate medical attention is not required. If symptoms persist, call a physician. Move to fresh air in case of accidental inhalation of vapors or decomposition products.
<b>Skin contact</b>	Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash off immediately with soap and plenty of water. Consult a physician if necessary. Immediate medical attention is not required. If skin irritation persists, call a physician.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Call a physician immediately. If symptoms persist, call a physician.
<b>Ingestion</b>	Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. Clean mouth with water and drink afterwards plenty of water. Call a physician.
<b>Self-protection of the first aider</b>	Use personal protective equipment as required Avoid contact with skin, eyes or clothing

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** None known.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to physicians** May cause sensitization of susceptible persons. Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

### 4.4. Reference to Other Sections

**Reference to other sections** Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Section 11: TOXICOLOGY INFORMATION.

# SAFETY DATA SHEET

DAMPFIX PU  
Revision Number 3

Revision date 01-Aug-2019  
Supersedes Date: 28-May-2018

## Section 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing media

**Suitable extinguishing media** Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Alcohol resistant foam.

**Unsuitable extinguishing media** No information available.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Keep product and empty container away from heat and sources of ignition. Risk of ignition.

### 5.3. Advice for firefighters

**Special protective equipment for fire-fighters** Wear self-contained breathing apparatus and protective suit.

## Section 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Evacuate personnel to safe areas. Pay attention to flashback. Take precautionary measures against static discharges.

### 6.2. Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so. Cover powder spill with plastic sheet or tarp to minimize spreading. Dike far ahead of spill for later disposal. Protect from moisture.

### Methods for cleaning up

Cover liquid spill with sand, earth or other non-combustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Sweep up and shovel into suitable containers for disposal. Soak up with inert absorbent material. Dam up. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges.

### 6.4. Reference to other sections

**Reference to other sections** Section 7: HANDLING AND STORAGE  
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION  
Section 13: DISPOSAL CONSIDERATIONS

## Section 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

**Advice on safe handling** Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take necessary action to avoid static electricity discharge (which might cause

# SAFETY DATA SHEET

DAMPFIX PU  
Revision Number 3

Revision date 01-Aug-2019  
Supersedes Date: 28-May-2018

ignition of organic vapors).

## 7.2. Conditions for safe storage, including any incompatibilities

**General hygiene considerations** When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Wash hands thoroughly after handling. Keep away from food, drink and animal feeding stuffs.

**Storage Conditions** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers. Protect from moisture. Protect from direct contact with water or excessive moisture. Keep from freezing.

**Incompatible materials** No information available

## 7.3. Specific end use(s)

**Specific Use(s)** Primers, Sealers, and Undercoaters.

**Other information** No information available.

## 7.4. References to Other Sections

**Reference to other sections** Section 13: DISPOSAL CONSIDERATIONS. Section 10: STABILITY AND REACTIVITY.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure Limits

Chemical name	New Zealand	Australia	European Union
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 50 ppm TWA: 217 mg/m <sup>3</sup>	80 ppm TWA 350 mg/m <sup>3</sup> TWA 150 ppm STEL 655 mg/m <sup>3</sup> STEL	TWA: 50 ppm TWA: 221 mg/m <sup>3</sup> STEL: 100 ppm STEL: 442 mg/m <sup>3</sup> *
Ethylbenzene 100-41-4	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	100 ppm TWA 434 mg/m <sup>3</sup> TWA 125 ppm STEL 543 mg/m <sup>3</sup> STEL	TWA: 100 ppm TWA: 442 mg/m <sup>3</sup> STEL: 200 ppm STEL: 884 mg/m <sup>3</sup> *
1-Methyl-2-pyrrolidone 872-50-4	TWA: 25 ppm TWA: 103 mg/m <sup>3</sup> STEL: 75 ppm STEL: 309 mg/m <sup>3</sup> Skin	25 ppm TWA 103 mg/m <sup>3</sup> TWA 75 ppm STEL 309 mg/m <sup>3</sup> STEL	TWA: 10 ppm TWA: 40 mg/m <sup>3</sup> STEL: 20 ppm STEL: 80 mg/m <sup>3</sup> *
Dibutyltin dilaurate 77-58-7	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.2 mg/m <sup>3</sup> Skin	0.1 mg/m <sup>3</sup> TWA 0.2 mg/m <sup>3</sup> STEL	-

Chemical name	ACGIH TLV	NIOSH IDLH	OSHA PEL
Xylenes (o-, m-, p- isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	-	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>
Benzene, 1,3-diisocyanatomethyl- 26471-62-5	STEL: 0.005 ppm inhalable fraction and vapor TWA: 0.001 ppm inhalable fraction and vapor S*	-	-
Ethylbenzene 100-41-4	TWA: 20 ppm	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>

# SAFETY DATA SHEET

DAMPFIX PU  
Revision Number 3

Revision date 01-Aug-2019  
Supersedes Date: 28-May-2018

Dibutyltin dilaurate 77-58-7	STEL: 0.2 mg/m <sup>3</sup> Sn TWA: 0.1 mg/m <sup>3</sup> Sn S*	IDLH: 25 mg/m <sup>3</sup> Sn TWA: 0.1 mg/m <sup>3</sup> except Cyhexatin Sn	TWA: 0.1 mg/m <sup>3</sup> Sn
---------------------------------	---	--	-------------------------------

**Derived No Effect Level (DNEL)** No information available

**Predicted No Effect Concentration (PNEC)** No information available

**OTHER INFORMATION** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

## PPE - Personal Protection Equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).  
**Skin and body protection** Wear suitable protective clothing. No special technical protective measures are necessary under normal conditions.  
**Hand protection** Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.  
**Respiratory protection** No protective equipment is needed under normal use conditions. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of professional filter is recommended.  
**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and wash before reuse.

**Environmental exposure controls** No information available.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

**Appearance** Thixotropic Paste  
**Color** Gray  
**Odor** Solvent  
**Odor threshold** No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	No data available °C	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	
Vapor density	No data available	
Relative density	No data available	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	20,000 - 100,000 mPa s	

# SAFETY DATA SHEET

DAMPFIX PU  
Revision Number 3

Revision date 01-Aug-2019  
Supersedes Date: 28-May-2018

**Explosive properties** No information available  
**Oxidizing properties** No information available

**9.2. Other information**

**Softening Point** No information available  
**Molecular weight** No information available  
**Solvent content (%)** No information available  
**Solid content (%)** No information available  
**Density** 1.23 g/cm<sup>3</sup>  
**Bulk density** No information available  
**VOC Content (%)** 187 g/L

## Section 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

**Reactivity** None under normal use conditions.

### 10.2. Chemical stability

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

**Hazardous polymerization** None under normal processing.

### 10.4. Conditions to avoid

**Conditions to avoid** Heat, flames and sparks. Protect from moisture.

### 10.5. Incompatible materials

**Incompatible materials** No information available.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions.

## Section 11: TOXICOLOGY INFORMATION

### 11.1. Information on toxicological effects

#### Acute Toxicity

**Product Information** Product does not present an acute toxicity hazard based on known or supplied information.

**Inhalation** No data available.  
**Eye contact** No data available.  
**Skin contact** No data available.  
**Ingestion** No data available.

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene 64742-48-9	> 6000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	LC50 Vapour (4h) >5020 mg/m <sup>3</sup> (Rat)
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Xylenes (o-, m-, p- isomers)	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350	= >47635 mg/L ( Rat ) 4 h =

# SAFETY DATA SHEET

DAMPFIX PU  
Revision Number 3

Revision date 01-Aug-2019  
Supersedes Date: 28-May-2018

1330-20-7		mg/kg ( Rabbit )	>5000 ppm ( Rat ) 4 h
Benzene, 1,3-diisocyanatomethyl-26471-62-5	= 3060 mg/kg ( Rat )	= 10000 mg/kg ( Rabbit )	= 0.107 mg/L ( Rat ) 4 h (Vapour)
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 1432 mg/L ( Rat ) 4 h
Benzenesulfonyl isocyanate, 4-methyl-4083-64-1	= 2234 mg/kg ( Rat )	LD 50 (Rat) > 2000 mg/kg OECD 402	> 640 ppm ( Rat ) 1 h
Glycidoxypropyltrimethoxysilane 2530-83-8	= 8025 mg/kg (rat)	= 4250 mg/kg ( Rabbit )	> 5.3 mg/L ( Rat ) 4 h
1-Methyl-2-pyrrolidone 872-50-4	= 3914 mg/kg ( Rat )	= 8 g/kg ( Rabbit )	> 5.1 mg/L ( Rat ) 4 h
Dibutyltin dilaurate 77-58-7	= 2071 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	-

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	No information available.
<b>Serious eye damage/eye irritation</b>	No information available.
<b>Sensitization</b>	No information available.
<b>Germ cell mutagenicity</b>	No information available.
<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	No information available.
<b>Target organ effects</b>	Eyes, Lungs, retina, Skin, liver.
<b>Aspiration hazard</b>	No information available.
<b>Carcinogenicity</b>	The following substance(s) are classified in Annex VI CLP (1272/2008) as carcinogenic.

Chemical name	IARC	China	Japan
Xylenes (o-, m-, p- isomers)	Group 3	-	-
Benzene, 1,3-diisocyanatomethyl-	Group 2B	-	Group 2B
Ethylbenzene	Group 2B	Possibly carcinogenic to humans	Group 2B

IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans Group 3 - Not Classifiable as to Carcinogenicity in Humans

## Section 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### Ecotoxicity

#### Product Information

Very toxic to aquatic life. Harmful to aquatic life.

#### Component Information

Data obtained on the component(s) include

Chemical name	Algae/aquatic plants	Fish	Crustacea
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene 64742-48-9	EL50 (72h) > 1000 mg/l (Pseudokirchneriella subcapitata) OECD 201	LC50: =2200mg/L (96h, Pimephales promelas)	LL50 (48h) > 1000 mg/l (Daphnia magna) OECD 202
Petroleum distillates, hydrotreated light 64742-47-8	-	LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncorhynchus mykiss) LC50: =45mg/L (96h, Pimephales promelas)	LC50: =4720mg/L (96h, Den-dronereides heteropoda)
Xylenes (o-, m-, p- isomers) 1330-20-7	-	LC50 96 h 2.6 mg/L (Oncorhynchus mykiss) (OECD 203)	EC50 48 h = 3.4 mg/L (water flea)
Urea, N,N'-(methylenedi-4,1-phenylene) bis[N'-butyl-77703-56-1	EC50 (72h) >100 mg/L Algae (Raphidocelis subcapitata)	LC50 (96h)>250 mg/L Fish (Brachydanio rerio)	EC50 (48h) >100 mg/L Daphnia magna
Ethylbenzene 100-41-4	EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static)	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)



# SAFETY DATA SHEET

DAMPFIX PU  
Revision Number 3

Revision date 01-Aug-2019  
Supersedes Date: 28-May-2018

Glycidoxypropyltrimethoxysilane 2530-83-8	-	LC50 (96h) = 55 mg/L (Cyprinus carpio) OECD 203	EC50 (48h) =473 mg/L Daphnia magna
1-Methyl-2-pyrrolidone 872-50-4	EC50: >500mg/L (72h, Desmodemus subspicatus)	LC50: =832mg/L (96h, Lepomis macrochirus) LC50: =1400mg/L (96h, Poecilia reticulata) LC50: =4000mg/L (96h, Leuciscus idus) LC50: =1072mg/L (96h, Pimephales promelas)	EC50: =4897mg/L (48h, Daphnia magna)
Dibutyltin dilaurate 77-58-7	-	LC50: =2mg/L (48h, Oryzias latipes)	-

## 12.2. Persistence and degradability

No information available.

## 12.3. Bioaccumulative potential

There is no data for this product.

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Petroleum distillates, hydrotreated light 64742-47-8	-	159
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15	15
Benzene, 1,3-diisocyanatomethyl- 26471-62-5	-	5
Ethylbenzene 100-41-4	3.2	15
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	0.6	-
1-Methyl-2-pyrrolidone 872-50-4	-0.46	-
Dibutyltin dilaurate 77-58-7	4.44	-

## 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene 64742-48-9	The substance is not PBT / vPvB
Petroleum distillates, hydrotreated light 64742-47-8	The substance is not PBT / vPvB
Xylenes (o-, m-, p- isomers) 1330-20-7	The substance is not PBT / vPvB
Urea, N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl- 77703-56-1	Further information relevant for the PBT assessment is necessary
Benzene, 1,3-diisocyanatomethyl- 26471-62-5	The substance is not PBT / vPvB
Ethylbenzene 100-41-4	The substance is not PBT / vPvB
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	The substance is not PBT / vPvB
Glycidoxypropyltrimethoxysilane 2530-83-8	The substance is not PBT / vPvB
1-Methyl-2-pyrrolidone 872-50-4	The substance is not PBT / vPvB PBT assessment does not apply
Dibutyltin dilaurate 77-58-7	The substance is not PBT / vPvB

## 12.6. Other adverse effects

# SAFETY DATA SHEET

DAMPFIX PU  
Revision Number 3

Revision date 01-Aug-2019  
Supersedes Date: 28-May-2018

No information available.  
**Endocrine Disruptor  
Information**

## Section 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste from residues/unused products** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

## Section 14: TRANSPORT INFORMATION

**IMDG** Not regulated

**IATA** Not regulated

**ADR** Not regulated

## Section 15: REGULATORY INFORMATION

### National Regulations

**ERMA Group** HSR002672

## Section 16: OTHER INFORMATION

### **Key or legend to abbreviations and acronyms used in the safety data sheet**

No information available

### **Key Literature References and Sources for Data**

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 01-Aug-2019

**Revision note** Not applicable.

**Training Advice** No information available

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**