



FILL A GAP[®] FLEXIBLE

HIGHLY FLEXIBLE, ACRYLIC GAP FILLER

27 February 2017

YOUR SMART ADVANTAGES

- Available in 7 popular colours
- Anti-fungal and anti-mould formulation
- High flexibility
- Non slump
- Cured sealant will dry to a similar colour as when wet
- Smooth finish with low shrinkage
- Water clean up
- Good adhesion to most building materials
- Environmentally friendly
- Low VOC

USES

Bostik Fill A Gap[®] Flexible is a highly flexible, anti-fungal, mildew resistant acrylic gap sealant. It offers excellent adhesion strength when cured and is more flexible than conventional acrylic gap sealants with minimal shrinkage. Bostik Fill A Gap Flexible can be used on:

- Interior and exterior applications
- Bathroom, kitchen and laundry areas
- Crack filling prior to painting
- Low movement joints between light partition walls
- Skirting boards
- Architraves
- Window frames
- Door frames
- Plasterboard
- Brick
- Concrete
- Aluminium
- Wood
- Glass

PRODUCT CHARACTERISTICS

Colour	7 popular colours
Viscosity	Smooth paste like consistency
Composition	Water based acrylic
Coverage	5mm bead: 15m per cartridge
Application temperature	5° C to 35°C

Product codes

300ml cartridge/12 per carton

White	30607681
Vanilla	30607683
Beige	30607684
Light Grey	30607682
Dark Grey	30607685
Chocolate Brown	30607686
Black	30607687

TYPICAL PERFORMANCE DATA (approx.)

Service temperature	-5°C to +75°C
Skin time	5 minutes
Full cure	2-3 days depending on temperature
Specific gravity	1.5
Total joint movement	± 10%
Maximum joint width	Up to 25mm in localized areas

DIRECTIONS FOR USE

Read and understand the Safety Data Sheet before using this product. SDS can be acquired by visiting www.bostik.com.au or by scanning the relevant QR code on pack.

SURFACE PREPARATION

For optimum performance, surfaces to be bonded should be clean, dry, and free of dust, wax, grease or any loose or flaking paint.

APPLICATION

1. Cut cartridge tip, fasten nozzle to cartridge and cut nozzle at 45° angle (approx. 5mm). Hold caulking gun at a 45° angle and squeeze trigger at even pressure.
2. While the caulk is being dispensed, move the caulking gun along the crack or gap at an even speed
3. Smooth off with wet finger or scrape off lightly with a wet putty knife.
4. Bostik Fill A Gap Flexible becomes touch dry within 30 minutes under normal conditions. Do not expose to water for up to 24 hours after application.

BOSTIK FILL A GAP® FLEXIBLE

LIMITATIONS

- Do not use to provide a seal where there is constant water pools, underwater, submerged joints, damp substrates, in trafficable areas or on absorptive surfaces (e.g. marble, limestone or granite)
- Do not use in external applications where rain is imminent within 4 hours
- Not recommended for use where abrasion or physical abuse can be expected
Not recommended for use when applied to substrates below 5°C, powder coated surfaces, damp substrates, trafficable applications or external expansion joints
- Not recommended for use where exposed to water or where water pools

CLEANING

Remove excess uncured sealant immediately with a damp cloth or water. Cured silicone is best removed by scraping or sanding. Use Bostik Handy Wipe towels to remove silicone from skin.

STORAGE AND SHELF LIFE

Store in cool (between 5°C to 25°C) dry, well-ventilated area out of direct sunlight. Shelf life is 24 months in original unopened container if stored below 25°C.

DISPOSAL

Empty cartridges may be disposed via local landfill. If spilt, absorb with clay, sand or earth. Collect and seal in properly labeled metal container. Dispose of according to local authority regulations. Do not dispose of down drains or into local waterways.

VOC INFORMATION

25g/litre

HEALTH AND SAFETY

Non-hazardous.

If poisoning occurs, contact Poisons Information Centre

FIRST AID

Swallowed: Do not induce vomiting, give a glass of water and contact a doctor immediately.

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Eyes: Hold eyes open and flood with water for at least 15 minutes.

For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.

BOSTIK HOTLINE

Smart help 1800 898 551



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com/au