



ACRYL S

Acrylic putty. Resumption of cracks. Caulking.

Seal before painting. Label SNJF Facade - plastic sealant class 12.5 P.

PRODUCT DESCRIPTION

Acrylic sealant for various caulking and crack repair before painting.

SNJF Label Front - acrylic sealant class 12.5 P.

Can be painted. Indoor / outdoor use.

- Heavy and light prefabrication.
- Caulking of partitions, frames of wood - aluminum or PVC with masonry.
- Sealing of wood or metal supports (windows).
- Finishing joints.
- Filling grooves between floorboards before implementation of a fiber-coated smoothing.

ADVANTAGES

Can be painted *.

Indoor / outdoor use.

Solvent-free, isocyanate-free

Great ease of extrusion.

Withstands temperatures from -20°C to +80°C.

Excellent adhesion without primer on concrete, aluminum, wood, masonry, PVC.

* Given the great diversity of paints on the market, it is essential to carry out compatibility tests

before any use on site of a product not yet tested.

WORKING INSTRUCTION

SUPPORTS

In all cases, the substrates will be clean, dry, healthy (non-dusty), dust-free and degreased.

On very porous substrates, it is possible to apply beforehand a dilution consisting of one volume of putty for two volumes of clean water. Brushing of the joint lips is recommended before application.

APPLICATION

Eliminate all friable or poorly adhered parts.

The mastic is put in place by extrusion, possibly on the bottom of the joint when necessary. After extrusion, tighten and smooth the bead of caulk within 10 minutes with a spatula dipped in soapy water. Avoid that this one does not be inserted between the sealant and the contact surfaces, in order to preserve a good adhesion. Let dry a few hours before finishing and carry out a test.

External grouting / filler must be done in dry weather.

Respect a 24 hours delay (for a temperature of + 20 ° C) before exposure of the seal to the water (rain or projections of water).

Caution: Cold and / or wet weather may slow or even prevent drying.

In general, refer to the DTU and professional rules in force.

Joint function: refer to DTU 44.1 Sealing facade joints using sealants.

CLEANING

- Fresh product: with water.
- Dry product: by scratching

CONSUMPTION

About 12 m of 5 mm diameter cord.

STORAGE

18 months in closed original packaging, stored frost free between + 5 ° C and + 30 ° C.

PACKAGING

Code	Packaging	Products per pallet	GENCOD
30136823	White - Cartridge 310 ml	12	35492100 30959
30136833	Gray - Cartridge 310 ml	12	35492100 30966
30136843	Brown - Cartridge 310 ml	12	35492100 30973

TECHNICAL DATA

Color: white - gray - brown

Open time / skin formation: 5 minutes

Dust free time: 30 minutes

Polymerisation speed: 2 mm / 24 h approx.

Shore hardness A: 15

Elongation at break:> 100%

Temperature of use: between + 5 ° C and + 40°C

Operating temperature: -20 ° C to + 80 ° C

CONTACT US

Bostik LLC

ООО «БОСТИК» 127018 г. Москва, ул. Двинцев, д.12, корп.1

Phone : (495) 787 31 71

Fax :(495) 787 31 72

E-mail : inforu@bostik.com

www.bostik.ru

Disclaimer : The technical data we present, as well as our instructions are recommendations are all based on a variety of tests and our experience. They are intended to help the user to find the most suitable working method and get the best possible results. Since the users working conditions is beyond our control, we cannot accept any responsibility for the results obtained by the product.

BOSTIK HOTLINE

Smart help +7 495 787 31 71



